

4XEM USB Type-C to HDMI Adapter

4XEM Part- 4XUSBCHDMIA



Easily connect your USB Type-C enabled device to an HDMI TV, projector or monitor with 4XEM's USB Type-C to HDMI cables. Featuring 10 Gbps high speed performance, a 120 Hz refresh rate and deep colour for 1080p resolution and beyond. 4XEM HDMI cables and adapters are 3D video capable and support 5.1 and 7.1 Dolby True HD and DTS-HD Lossless Surround Sound for brilliant and clear audio. Molded gold-plated connectors and double shielding provide superior connectivity and rejection of EM and RF interference.

Problem it solves: Get the big screen experience! The ideal cable for sharing your vacation videos or Arrested Development episodes on your HDMI-equipped TV, monitor or external projectors.

4XEM gear is respected industry wide for its high performance, premium quality and durability.

4XEM Products Are Available At Your Favorite Online Retailers
WWW.4XEM.COM Contact Todd Schaus 4XEM sales Rep
1-866-999-4936 Ext.104 tschaus@4xem.com



Features

- Plug and play with no adapters or software/drivers
- Compatible with USB-C port (Thunderbolt 3 compatible)
- Supports resolutions up to 4K @60Hz
- Superior high-performance connection
- Fully compatible with the new iPad Pro and MacBook Air

Application

- Home office
- Small business
- Home Theatre
- Mirror or Extend Multiple Displays

4XEM Products Are Available At Your Favorite Online Retailers



| | | |
|--------------------------|-----------------------------|---|
| Warranty Information | Warranty | 1 Year |
| Hardware | Active or Passive Adapter | Active |
| | Chip ID | |
| | Direction | Unidirectional |
| | Adapter Style | Port-Saver |
| | Audio | Yes |
| | AV Input | DisplayPort 1.2 (via USB-C connector) |
| | AV Output | HDMI 2.0 |
| Performance | Maximum Digital Resolutions | 4K UHD (4096 x 2160 @ 60Hz) |
| | Audio Specifications | 7.1 ch |
| Connector(s) | Connector A (Source) | 1 - USB Type-C (24 pin) Male Input |
| | Connector B (Display) | 1 - HDMI (19 pin) Female Output |
| Power | Power Source | Bus Powered |
| Environmental | Humidity | 40%~50%RH |
| | Operating Temperature | 0°C to 70°C (32°F to 158°F) |
| | Storage Temperature | -10°C to 55°C (14°F to 131°F) |
| Physical Characteristics | Colour | White |
| | Cable Length | 3.2 in [81 mm] |
| | Overall Length | 6.65 in [169 mm] |
| | Cable OD | 0.18 in [4.5 mm] |
| | Weight of Product | 0.6 oz [18 g] |
| Packaging Information | Shipping (Package) Weight | 0.9 oz [26 g] |
| | Package Height | 9.25 in [235 mm] |
| | Package Width | 4.96 in [126 mm] |
| | Package Length | 0.71 in [18 mm] |
| What's in the Box | Included in Package | 1 - USB-C to HDMI Adapter |
| Notes | Notes | DisplayPort Alt Mode support required from host device Compatible with Thunderbolt 3 ports |
| Country of Origin | Country of Origin | China |

* Product appearance and specifications are subject to change without notice.

* Same day shipping is only available for orders shipping within the United States.

4XEM Products Are Available At Your Favorite Online Retailers

