

4XEM's 3-in-1 USB-C Docking Station with VGA port and USB 3.0

4XEM Part- 4XUSBCHUB03



Introducing the 4XEM 3-in-1 USB-C Docking Station with VGA port and USB 3.0 – your ultimate solution for seamless connectivity and power management.

Experience the brilliance of 4K support with the ability to connect a single display, achieving crystal-clear resolutions that bring your content to life. Equipped with 1 USB port, this hub facilitates quick and efficient data transfer at up to 5 Gbps, enhancing your workflow. Its power delivery pass-thru feature allows up to 100W of power, ensuring your devices stay juiced up and ready to go.

Crafted with industry-leading chipset IDs, this docking station adheres to Power Delivery (PD 2.0) standards, providing efficient power management. The USB 3.1 Gen 1 (5Gbps) host bus type ensures rapid data transfer, while the fixed attached USB Type-C cable guarantees a stable connection.

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

**Contact Todd Schaus 4XEM sales Rep
1-866-999-4936 Ext.104 tschaus@4xem.com**



Features:

- Fixed Attached USB-C cable
- USB 3.1 Gen 1 5 Gbps Host connector
- 1x VGA port
- 1x USB Type-A (5 Gbps) port
- 1x USB Type-C (USB PD only) port
- Supports 4K video resolutions
- Meets Power Delivery 2.0 standards and offers PD pass-thru up to 100W
- Compatible with Windows 10 and Mac OS 11
- 5W power consumption



Application

- Home
- Office
- Networks
- Charging
- Transferring



4XEM Products Are Available At Your Favorite Online Retailers



Warranty Information	Warranty	3 Years
Features	4K Support	Yes
	Displays Supported	1
	USB Ports	1
	Fast-Charge Port(s)	No
	Network	No
	Media Card Reader	No
	Audio	No
	Power Delivery	Pass-thru, up to 100w
Hardware	Chipset ID	Realtek - RTD2166 Fresco Logic - FL7102
	Industry Standards	Power Delivery (PD 2.0)
Connector(s)/Performance	Host Bus Type	USB 3.1 Gen 1 (5Gbps)
	Host Connector	USB Type-C
	Host Connector Type	Fixed Attached Cable
	Connector Type(s)/Rate(s)	1x VGA
		1x USB Type-A (5 Gbps)
	1x USB Type-C (No Data - USB-PD Input Only)	
	Maximum Digital Resolutions	N/A
	Maximum Analog Resolutions	1920 x 1080 @ 60Hz, 8bpc
	Audio Specifications	N/A
Software	OS Compatibility	Windows® 10 Mac OS® 11
Power	Power Source	Bus Powered
	Power Consumption	5W
	Power Delivery	PD Pass-Through - Max 100W
		5VDC @ 3.00A
		9VDC @ 3.00A
		12VDC @ 3.00A
15VDC @ 3.00A		
20VDC @ 5.00A		
Physical Characteristics	Colour	Silver, White
	Shell Material	Aluminum & Plastic
	LED Indicators	None
	Attached Cable Length	2.95 in [75.0 mm]
	Product Height	0.60 in [15.3 mm]
	Product Width	2.93 in [74.3 mm]
	Product Length (Body)	1.29 in [38.2 mm]
	Product Length (Overall)	6.00 in [152.5 mm]
	Weight of Product	2.05 oz [58 g]
Environmental	Operating Temperature	14°F to 113°F [-10°C to 45°C] @ 5%-95% RH (Non-Condensing)
	Storage Temperature	-4°F to 149°F [-10°C to 65°C] @ 5%-95% RH (Non-Condensing)
Packaging Information	Package Type	Poly-Bag
	Package Height	9.74 in [247.5 mm]
	Package Width	5.12 in [130.0 mm]
	Package Length	0.61 in [15.5 mm]
	Shipping (Package) Weight	2.26 oz [64 g]
What's in the Box	Included in Package	1x USB-C Hub
	Requirements	DP-Alt mode and USB-PD support from host required to ensure full functionality.
Notes	Notes	Some hardware may have specific power requirements. For example, if your laptop expects 60W of power and an adapter consumes some of the 60W, your hardware/operating system may display a "slow charging" message.

* Product appearance and specifications are subject to change without notice.

* Same day shipping is only available for orders shipping within the United States.

