

4XEM 4-in-1 HDMI, VGA, Power Delivery USB-C Hub

4XEM Part- 4XUSBCHUB05



Expand your desktop to multiple displays with higher resolutions for an increased experience when entertaining, gaming, and when at work. 4XEM's 4-in-1 USB-C Docking Station connects to a multitude of devices through its HDMI port and VGA port. Additionally, the docking station comes with a USB-C port and a USB-A port which comes with Power Delivery; both ideal for charging and transferring data. Increase your displays either at work or at leisure with 4XEM's 4-in-1 USB-C Docking Station.

Problem it Solves: The 4XEM's 4-in-1 USB-C Docking Station allows you to expand your desktop monitor to other screens, either through an HDMI connection or a VGA one. Get higher resolution simply with 4XEM's 4-in-1 Docking Station.

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep
1-866-999-4936 Ext.104 tschaus@4xem.com



Features:

- Fixed Attached USB 3.0 Type-C Host connector cable
- Meets Power Delivery 2.0 standards with PD Pass through – Max 100W in/90W out
- Meets HDMI 1.4 industry standard
- 1x HDMI 1.4 (10.2 Gbps) port
- 1x VGA port
- 1x USB 3.0 Type-A (5 Gbps) port
- 1x USB Type-C (for PD only) port
- Supports 4K single display video
- Supports 2 Display video (not 4K simultaneously)
- Compatible with Windows 10 and Mac OS 11
- PC Compatibility: MacBook Pro 15"/13"/2018/17/16, MacBook 2018/17/16/15, iMac/iMac Pro 2017, Dell XPS 13 9350/9360, HUAWEI MateBook X
- Mobile Compatibility: Huawei mate 10/P20, Samsung Galaxy S8/S8+/S9/S9+

Application

- Home
- Office
- Networks
- Charging
- Transferring



4XEM Products Are Available At Your Favorite Online Retailers



Warranty Information	Warranty	3 Years
Features	4K Support Displays Supported USB Ports Fast-Charge Port(s) Network Media Card Reader Audio Power Delivery	Yes 2** 1 No No No Yes* Pass-thru, up to 100w in/90w out
Hardware	Chipset ID Industry Standards	Explore Microelectronics - EP9632 HDMI 1.4 Power Delivery (PD 2.0)
Connector(s)/Performance	Host Bus Type Host Connector Host Connector Type Connector Type(s)/Rate(s) Maximum Digital Resolutions Maximum Digital Resolutions Audio Specifications	USB 3.1 Gen 1 (5Gbps) USB 3.0 Type-C (5 Gbps) Fixed Attached Cable 1x HDMI 1.4 (10.2 Gbps) 1x VGA 1x USB 3.0 Type-A (5 Gbps) 1x USB Type-C (used for PD only) Single Display: 3840 x 2160 @ 30Hz Dual Display: 1920 x 1080 @ 60Hz 1920 x 1080 @ 60Hz 2-ch Stereo (via HDMI)
Software	OS Compatibility	Windows® 10 Mac OS® 11
Power	Power Source Power Consumption Power Delivery	Bus Powered 10W PD Pass-Through - Max 100W In/90W Out 5VDC @ 1.50A 9VDC @ 2.40A 12VDC @ 2.40A 15VDC @ 2.60A 20VDC @ 4.50A
Physical Characteristics	Color Shell Material LED Indicators Attached Cable Length Product Height Product Width Product Length (Body) Product Length (Overall) Weight of Product	Grey, Black Aluminum, Plastic None 2.20 in [55.9 mm] 0.62 in [15.7 mm] 2.43 in [61.6 mm] 1.79 in [45.5 mm] 5.65 in [143.5 mm] 1.48 oz [42 g]
Environmental	Operating Temperature Storage Temperature	14°F to 113°F [-10°C to 45°C] @ 5%-95% RH (Non-Condensing) -4°F to 149°F [-10°C to 65°C] @ 5%-95% RH (Non-Condensing)
Packaging Information	Package Type Package Height Package Width Package Length Shipping (Package) Weight	Poly-Bag 6.63 in [168.4 mm] 3.00 in [76.2 mm] 0.73 in [18.5 mm] 1.98 oz [56 g]
What's in the Box	Included in Package	1x USB-C Hub
Notes / Special Requirements	Requirements Notes	DP-Alt mode and USB-PD support from host required to ensure full functionality. "Adapter does NOT function as an MST hub. When 2 displays are connected simultaneously, the host OS will only recognize a single display and video output is mirrored. When VGA is connected, the max resolution of HDMI drops to 1080p @ 60Hz, 8bpc. Audio output via HDMI only."

* Product appearance and specifications are subject to change without notice.

* Same day shipping is only available for orders shipping within the United States.

