

4XEM 6-in-1 4 HDMI port USB-C Dock

4XEM Part- 4XUSBCHUB09



4XEM's USB-C Docks are designed to improve the capabilities of your single monitor displays and laptops. 4XEM's 6-in-1 4 HDMI port USB-C Dock offers a unique opportunity to vastly expand your display capabilities. Fitted with 4 HDMI ports, capable of supporting 4K video resolution, this 6-in-1 device can connect a whole host of displays into one comprehensive network. Either connect one display to two or use this device to serve as a hub to multiple displays and device. Additionally, fitted with USB-A and USB-C ports this device is also able to charge and transfer data through USB enabled device.

Problem it solves: Create a comprehensive hub for 4 HDMI enabled devices or expand your laptop or single monitor displays swiftly with 4XEM's 6-in-1 4 HDMI Port USB-C Dock.

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep
1-866-999-4936 Ext.104 tschaus@4xem.com



Features:

- Detachable USB Type-C Host connector cable
- Bus Powered – USB 3.1 Gen 1 bus type
- Meets HDMI 1.4 and HDCP 1.4 industry standards
- Meets Power Delivery 2.0 standards with PD pass through – Max 100W in/55W out
- 4x HDMI 1.4 (10.2 Gbps) ports
- 1x USB 3.0 Type-A (5 Gbps) port
- 1x USB Type-C port (PD use only)
- Supports 4K UHD video
- Supports up to 4 displays (not 4K simultaneously)
- LED indicators for power and network connection
- Compatible with Windows 10 and Mac OS 11
- DP alt Mode required by host to ensure full video functionality

Front

Back

Application

- Home
- Office
- Networks
- Charging
- Transferring



4XEM Products Are Available At Your Favorite Online Retailers



Warranty Information	Warranty	3 Years
Features	4K Support Displays Supported USB Ports Fast-Charge Port(s) Network Media Card Reader Audio Power Delivery	Yes 4** 1 No No No No Pass-thru, up to 100w in/55w out
Hardware	Chipset ID Industry Standards	Algotek - AG9311 Lontium Semiconductor - LT86104SX HDMI 1.4 HDCP 1.4 Power Delivery (PD 2.0)
Connector(s)/Performance	Host Bus Type Host Connector Host Connector Type Connector Type(s)/Rate(s) Maximum Digital Resolutions Maximum Analog Resolutions Audio Specifications	USB 3.1 Gen 1 (5Gbps) USB Type-C Detachable Cable 4x HDMI 1.4 (10.2 Gbps) 1x USB 3.0 Type-A (5 Gbps) 1x USB Type-C (used for PD only) 4K UHD (3840 x 2160 @ 30Hz, 8bpc) N/A N/A
Software	OS Compatibility	Windows® 10 Mac OS® 11
Power	Power Source Power Consumption Power Delivery	Bus Powered 45W PD Pass-Through - Max 100W In/55W Out 5VDC @ 0.90A 9VDC @ 2.44A 12VDC @ 2.58A 15VDC @ 3.00A 20VDC @ 2.75A
Physical Characteristics	Color Shell Material LED Indicators Host Cable Length Product Height Product Width Product Length Weight of Product	Grey Aluminum Power: Blue Active HDMI out: Blue (x4) 38.27 in [972 mm] 0.62 in [15.7 mm] 4.72 in [120.0 mm] 2.21 in [56.2 mm] 3.81 oz [108 g]
Environmental	Operating Temperature Storage Temperature	14°F to 113°F [-10°C to 45°C] @ 5%-95% RH (Non-Condensing) -4°F to 149°F [-10°C to 65°C] @ 5%-95% RH (Non-Condensing)
Packaging Information	Package Type Package Height Package Width Package Length Shipping (Package) Weight	Box 6.85 in [174 mm] 3.00 in [76.2 mm] 0.73 in [18.5 mm] 5.50 oz [156 g]
What's in the Box	Included in Package	1x USB-C Hub 1x USB Type-C to Type-C Cable
Notes / Special Requirements	Requirements Notes	DP-Alt mode and USB-PD support from host required to ensure full functionality. *Adapter does NOT function as an MST hub. When multiple displays are connected simultaneously, the host OS will only recognize a single display and video output on all connected displays mirror each other. Some hardware may have specific power requirements. For example, if your laptop expects 60W of power and an adapter consumes some of the 60W, your hardware/operating system may display a "slow charging" message."
* Product appearance and specifications are subject to change without notice.		
* Same day shipping is only available for orders shipping within the United States.		

