

4XEM's 140W Wall Charger Quintuple Output w/ display

4XEM Part- 4XGAN016140WB



4XEM's 140W USB-C Charger offers amazing charging power and speed with five USB ports capable of charging a variety of devices simultaneously. USB-A has long been a standard port allowing for charging or power to legacy and current devices; however, USB-C is rapidly becoming a new standard for charging devices, allowing for up to 140W charging for power at faster speeds. This device features 3x USB-C ports and 2x USB-A port. Keep your USB devices charged on the go or at home reliably with 4XEM's USB-C and A Charger.

Problem it solves: Charge one to three USB devices with reliable power and speed using 4XEM's 140W GaN Charger.

**4XEM Products Are Available At Your Favorite Online Retailers**

**WWW.4XEM.COM**

Contact Todd Schaus 4XEM sales Rep  
1-866-999-4936 Ext.104 [tschaus@4xem.com](mailto:tschaus@4xem.com)



## Features:

- 140-Watt power budget
- 3x USB-C port
- 2x USB-A port
- Wall mounted charger
- Compatible with any USB charged device
- Compact travel size
- Rounded edges
- Fast Charging
- Power Output Display Hub

## Applications:

- Home
- Office
- Travel
- Meetings
- Classrooms
- Quick Charging



**4XEM Products Are Available At Your Favorite Online Retailers**





## DATA SHEET

Warranty Information	Warranty	1 Year
Connector(s)	Charging Port(s)	3x USB Type-C Female 2x USB Type-A Female
	Power Source	Non-Polarized NEMA 1-15P (Standard NA Wall Outlet) Fixed with Retractable Prongs
Performance	Industry Standards Certifications	USB-PD 3.0 CE FCC
Physical Characteristics	Colour	Black
	Display	Yes
	LED Indicator(s)	None
	Power Cable Length	N/A
	Product Height	3.36 in [85.4 mm]
	Product Width	1.22 in [31.1 mm]
	Product Length	3.00 in [76.3 mm]
Weight of Product		3.63 in [92.1 mm] (with power prongs out)
		10.23 oz [290 g]
Power	Total Power Budget	140W
	Power Delivery	100W Max
	Input Voltage	100-240VAC, 50Hz-60Hz @ 2.5A
	Output Voltage (C1/C2/C3)	100W: 5/9/12/15V 3A, 20V 5A
	Output Voltage (A1/A2)	60W: 5/9/12/20V 3A
	Output Voltage (C1/C2) + (C2/C3)	140W MAX - 95W: 5/9/12/15 3A, 20V 4.75A + 45W: 5/9/12/15V 3A, 20V 2.25A
	Output Voltage (A1) + (A2)	24W MAX - 12W: 5V 2.4A + 12W: 5V 2.4A
	Output Voltage (C1/C2/C3) + (A1/A2)	136W MAX - 100W: 5/9/12/15V 3A, 20V 5A + 36W: 5/9 3A, 12 2.5A, 20V 1.5A
	Output Voltage (C1/C2/C3) + (A1) + (A2)	124W MAX - 100W: 5/9/12/15V 3A, 20V 5A + 12W: 5V 2.4A + 12W: 5V 2.4A
	Output Voltage (C1) + (C2) + (C3)	140W MAX - 65W: 5/9/12/15V 3A, 20V 3.25A + 45W: 5/9/12/15V 3A, 20V 2.25A + 30W: 5/9V 3A, 12V 2.5A, 15V 2A, 20V 1.5A
	Output Voltage (C1/C2) + (C2/C3) + (A1/A2)	135W MAX - 65W: 5/9/12/15V 3A, 20V 3.25A + 45W: 5/9/12/15V 3A, 20V 2.25A + 25W: 5 3A, 9 2.5A, 12V 2A, 20V 1.25A
Output Voltage (C1/C2) + (C2/C3) + (A1) + (A2)	134W MAX - 65W: 5/9/12/15V 3A, 20V 3.25A + 45W: 5/9/12/15V 3A, 20V 2.25A + 12W: 5V 2.4A + 12W: 5V 2.4A	
Output Voltage (C1) + (C2) + (C3) + (A1/A2)	140W MAX - 65W: 5/9/12/15V 3A, 20V 3.25A + 30W: 5/9V 3A, 12V 2.5A, 15V 2A, 20V 1.5A + 20W: 5V 3A, 9V 2.22A, 12V 1.67A, 15V 1.33A + 25W: 5 3A, 9 2.5A, 12V 2A, 20V 1.25A	
Output Voltage (C1) + (C2) + (C3) + (A1) + (A2)	139W MAX - 65W: 5/9/12/15V 3A, 20V 3.25A + 30W: 5/9V 3A, 12V 2.5A, 15V 2A, 20V 1.5A + 20W: 5V 3A, 9V 2.22A, 12V 1.67A, 15V 1.33A + 12W: 5V 2.4A + 12W: 5V 2.4A	
Environmental	Operating Temperature	32°F to 104°F [0°C to 40°C]
	Storage Temperature	-4°F to 176°F [-20°C to 80°C]
	Humidity	5% to 90% (non-condensing)
Packaging Information	Package Type	Poly-Bag
	Package Height	7.00 in [177.8 mm]
	Package Width	5.00 in [127.0 mm]
	Package Length	1.23 in [31.3 mm]
	Shipping (Package) Weight	10.37 oz [294 g]
What's in the Box	Included in Package	1x 140W USB GaN Charger

\* Product appearance and specifications are subject to change without notice.  
\* Same day shipping is only available for orders shipping within the United States.

**4XEM Products Are Available At Your Favorite Online Retailers**

**WWW.4XEM.COM**

**Contact Todd Schaus 4XEM sales Rep  
1-866-999-4936 Ext.104 tschaus@4xem.com**

