

RTF LINE

Impastatrice a spirale con testa ribaltabile e vasca fissa

Spiral mixer with lifting top and fixed bowl





Maniglia di apertura ergonomica / Ergonomic handle



Sistema di apertura e **chiusura rapida Easy-Up** della testa
Easy-Up system for fast opening and closing of the head

Caratteristiche

- Vasca, spirale, spaccapasta in acciaio inox 304
- Disponibile in versione a 1 e 2 velocità sia monofase che trifase
- Trasmissione a catena con motoriduttore a bagno d'olio per riduzione della rumorosità
- Stop di emergenza attivato da sollevamento griglia
- Testa ribaltabile con pistone a gas per un sollevamento controllato e sicuro
- Timer e ruote di serie

Features

- Bowl, spiral, dough breaker in stainless steel 304
- Available with 1 and 2 speed both monophase and triphase
- Chain transmission with gearmotor in oil bath to reduce the operating noise.
- Emergency stop activated by lifting the protection grid.
- Lifting head with gas activated piston for a safe and soft lifting.
- Timer and wheels included

Disponibilità di motori con frequenza a 60HZ, certificati UL ed a 240V con spina inglese.

Availability of motors with 60HZ frequency, UL certified and 240V with english plug.

+ 9,5 cm



Ruote e timer di serie
Castors and timer included



Versione Trifase
Threephase version

RTF 20

VOLUME VASCA BOWL VOLUME	CAPACITÀ CAPACITY	DIMENSIONE VASCA cm DIMENSIONS CUVE cm	DIMENSIONI ESTERNE cm OUTSIDE DIMENSIONS cm	DIMENSIONI IMBALLO cm PACKAGE DIMENSIONS cm
21 lt	17 Kg	36 Ø 21 h	39 67 67 h	45 77 84 h

RTF 20 TR _ 400 V

TRIFASE
THREEPHASE

RTF 20 MO _ 230 V

MONOFASE
MONOPHASE

	POTENZA - POWER	PESO - WEIGHT	RPM		COD.
RTF 20 TR	1 Hp / 0,75 KW	71 Kg	85	10	7010133020
RTF 20 MO	1 Hp / 0,75 KW	71 Kg	85	10	7010123020
RTF 20 TR 2V	1/1,5 Hp / 0,75/1,1 KW	71 Kg	85/170	10/20	7010143020

RTF 20 TR 2V _ 400 V

TRIFASE 2 VELOCITÀ
THREEPHASE 2 SPEED

RTF 30

VOLUME VASCA BOWL VOLUME	CAPACITÀ CAPACITY	DIMENSIONE VASCA cm DIMENSIONS CUVE cm	DIMENSIONI ESTERNE cm OUTSIDE DIMENSIONS cm	DIMENSIONI IMBALLO cm PACKAGE DIMENSIONS cm
32 lt	25 Kg	40 Ø 26 h	43 74 75 h	51 79 93 h

RTF 30 TR _ 400 V

TRIFASE
THREEPHASE

RTF 30 MO _ 230 V

MONOFASE
MONOPHASE

	POTENZA - POWER	PESO - WEIGHT	RPM		COD.
RTF 30 TR	1,5 Hp / 1,1 KW	99 Kg	92	10	7010133130
RTF 30 MO	1,5 Hp / 1,1 KW	99 Kg	92	10	7010123130
RTF 30 TR 2V	1,7/2,5 Hp / 1,25/1,8 KW	99 Kg	92/184	10/20	7010143130

RTF 30 TR 2V _ 400 V

TRIFASE 2 VELOCITÀ
THREEPHASE 2 SPEED

RTF 40

VOLUME VASCA BOWL VOLUME	CAPACITÀ CAPACITY	DIMENSIONE VASCA cm DIMENSIONS CUVE cm	DIMENSIONI ESTERNE cm OUTSIDE DIMENSIONS cm	DIMENSIONI IMBALLO cm PACKAGE DIMENSIONS cm
41 lt	36 Kg	45 Ø 26 h	48 81 77 h	57 85 94 h

RTF 40 TR _ 400 V

TRIFASE
THREEPHASE

RTF 40 TR 2V _ 400 V

TRIFASE 2 VELOCITÀ
THREEPHASE 2 SPEED

RTF 40 MO _ 230 V

MONOFASE
MONOPHASE

	POTENZA - POWER	PESO - WEIGHT	RPM		COD.
RTF 40 TR	1,5 Hp / 1,1 KW	114 Kg	92	10	7010133040
RTF 40 MO	1,5 Hp / 1,1 KW	114 Kg	92	10	7010123040
RTF 40 TR 2V	1,7/2,5 Hp / 1,25/1,8 KW	114 Kg	92/184	10/20	7010143040

RTF 50

VOLUME VASCA BOWL VOLUME	CAPACITÀ CAPACITY	DIMENSIONE VASCA cm DIMENSIONS CUVE cm	DIMENSIONI ESTERNE cm OUTSIDE DIMENSIONS cm	DIMENSIONI IMBALLO cm PACKAGE DIMENSIONS cm
48 lt	43 Kg	45 Ø 30 h	48 81 77 h	57 85 94 h

RTF 50 TR _ 400 V

TRIFASE
THREEPHASE

RTF 50 TR 2V _ 400 V

TRIFASE 2 VELOCITÀ
THREEPHASE 2 SPEED

RTF 50 MO _ 230 V

MONOFASE
MONOPHASE

	POTENZA - POWER	PESO - WEIGHT	RPM		COD.
RTF 50 TR	2 Hp / 1,5 KW	136 Kg	92	10	7010133050
RTF 50 MO	2 Hp / 1,5 KW	136 Kg	92	10	7010123050
RTF 50 TR 2V	2/3 Hp / 1,5/2,2 KW	136 Kg	92/184	10/20	7010143050