



A / C / C PERFORMANCE SHAFT

SPINE	OUTER DIAMETER	INNER DIAMETER	GPI	LENGTH	TIPS	STRAIGHTNESS
350	6,06	3,9 mm	10,87	32"	100-120 gr.	+/- 0015
400	5,88	3,9 mm	9,81	32"	100-120 gr.	+/- 0015
450	5,77	3,9 mm	9,13	32"	100-120 gr.	+/- 0015
500	5,68	3,9 mm	8,66	32"	100-120 gr.	+/- 0015
550	5,61	3,9 mm	8,28	32"	100-120 gr.	+/- 0015
600	5,52	3,9 mm	7,81	31"	80-100 gr.	+/- 0015
650	5,46	3,9 mm	7,56	31"	80-100 gr.	+/- 0015
700	5,41	3,9 mm	7,10	31"	80-100 gr.	+/- 0015
750	5,38	3,9 mm	6,93	31"	80-100 gr.	+/- 0015
800	5,32	3,9 mm	6,75	31"	80-100 gr.	+/- 0015
850	5,30	3,9 mm	6,50	30"	60-80 gr.	+/- 0015
900	5,23	3,9 mm	6,19	30"	60-80 gr.	+/- 0015
1000	5,17	3,9 mm	5,94	30"	60-80 gr.	+/- 0015



POWERED BY



A / C / C PERFORMANCE SHAFT

Recurve Bow Weight	Draw Length AMO "										Compound Bow Weight	
	23"	24"	25"	26"	27"	28"	29"	30"	31"	32"	Medium Cam	Hard Cam
17-32"				1000R	900R 900C	850R 800C	800R 700C	750R 650C	700R 600C	650R 550C	25-30#	20-25#
24-29"			1000R	900R 900C	850R 800C	800R 700C	750R 650C	700R 600C	650R 550C	550R 500C	30-35#	25-30#
30-35"			900R 900C	850R 800C	800R 700C	750R 650C	700R 600C	650R 550C	550R 500C	500R 450C	35-40#	30-35#
36-40"		900R 900C	850R 800C	800R 700C	750R 650C	700R 600C	650R 550C	550R 500C	500R 450C	450R 400C	40-45#	35-40#
41-45"	900R 900C	850R 800C	800R 700C	750R 650C	700R 600C	650R 550C	550R 500C	500R 450C	450R 400C	400R 400C	45-50#	40-45#
46-50"	850R 800C	800R 700C	750R 650C	700R 600C	650R 550C	550R 500C	500R 450C	450R 400C	400R 400C	400R 400C	50-55#	45-50#
51-55"	800R 700C	750R 650C	700R 600C	650R 550C	550R 500C	500R 450C	450R 400C	400R 400C	400R 400C	400R 350C	55-60#	50-55#
56-60"	750R 650C	700R 600C	650R 550C	550R 500C	500R 450C	450R 400C	400R 400C	400R 400C	400R 350C	350R 350C	60-65#	55-60#
61-65"	700R 600C	650R 550C	550R 500C	500R 450C	450R 400C	400R 400C	400R 400C	400R 350C	350R 350C	350R 350C	65-70#	60-65#
66-70"	650R 550C	550R 500C	500R 450C	450R 400C	400R 400C	400R 400C	400R 350C	350R 350C	350R 350C	350R 350C	70-75#	65-70#

POWERED BY

