

## **Technical Specification**



**Product Code: ECSPK2** 

**Description:** Smart Security Alarm Kit with Hub, 2x PIRs, Door Contact and Remote Fob



#### Supplied

Fort Hub Fort PIR x 2 Fort Door/Window Contact Fort Remote Control AC Adapter Product Batteries Mounting Screws & Wall plugs User Guides

Compone	ent 1	Quantity
FOODLID	Occasi Alexand II In 19th Dellar Beat	

|--|

General Information	
Dimensions (mm)	109.5 x 109.5 x 40
Finish	White
Materials	ABS
Mounting	Surface
Available Operations	Home/Arm/Disarm/SOS
Sounder Output (dB)	95
Maximum Devices	32
Transmission Frequency (MHz)	433
Weight (Kg)	0.25
Supply & Power	
Operating Voltage (V DC)	12
Power Consumption (A)	1
Battery Specification	7.4V 600mAh Lithium Polymer
Power Reserve	8 Hours (Approx.)

#### **Transmission**

**Router Transmission Frequency (GHz)** 2.4 (IEEE 802.11 b/g/n) Router Transmission Range (m) 150

### Auxillary

GSM	Yes (Full-size SIM Card)
GSM Frequency (MHz)	850, 900, 1800 & 1900
Environment	

### Operating Temperature (°C) -10 to 55

Component 3	Quantity
ECSPCT - Smart Door / Window Contact Sensor	1

General	Information	

Dimensions (mm)	55.7 x 30.3 x 16
Finish	White
Materials	ABS
Mounting	Surface
Magnet Dimensions (mm)	25 x 10 x 9
Transmission Frequency (MHz)	433
Operating Voltage (V DC)	3
Power Consumption (A)	0.015
Battery Type	CR2477
Power Reserve	12 Months (Approx.)
Zone Types	Normal Sensor/24h mode/Delay mode/Home mode/24h mute sensor/ Home delay mode
Operating Temperature (°C)	-10 to 55
Relative Humidity Resistance (%)	<80 (non-condensing)
Weight (Kg)	0.2

Unit 7 Target Park, Shawbank Road, Lakeside, Redditch B98 8YN United Kingdom **T:** +44 (0)1527 515150 | **F:** +44 (0)1527 515143 E: info@espuk.com | W: espuk.com

	Quantity
ECSPPIR - Smart Security PIR	2

General Information	
Dimensions (mm)	107 x 53 x 32
Bracket Dimensions (mm)	52 x 30 x 26.5
Finish	White
Mounting	Surface
PIR Range (m)	8
Transmission frequency (MHz)	433
Operating Voltage (V DC)	3
Power Consumption (A)	0.0095
Battery Type	AA (LR06) x 3
Power Reserve	12 Months (Approx.)
Zone Types	Normal Sensor/24h mode/Delay mode/ Home mode/24h mute sensor/Home delay mode
Operating Temperature (°C)	-10 to 55
Relative Humidity Resistance (%)	<80 (non-condensing)
Weight (Kg)	0.046

#### Quantity Component 4 ECSPRC - Smart Alarm Remote Control

General	Information
	Dime

57 x 31 x 11
Black
ABS
Home/Arm/Disarm/SOS
433
3
CR 2025
<7
12 Months (Approx.)
-10 to 55
<80 (non-condensing)
0.02





# **Technical Specification**

ESP. Scolmoregroup

**Product Code: ECSPK2** 

**Description:** Smart Security Alarm Kit with Hub, 2x PIRs, Door Contact and Remote Fob

Warranty Years 1

