

ANTIQUÉ LIQUID RELEASE

PRODUCT CODE: 010-LIQRA

BUBBLE GUM SCENTED DECORATIVE CLEAR LIQUID RELEASE AGENT

PRODUCT DESCRIPTION

Antique Liquid Release is a bubble gum scented colorless liquid release agent specially formulated as a bond-breaker between freshly poured concrete and decorative tools such as stamp mats, texture skins, stencils, etc. It creates a lubricating barrier that extends the life of the texturing tools by decreasing the friction between the concrete and the tools. **Antique Liquid Release** evaporates leaving no residue behind, meaning less clean-up and labor cost. This characteristic makes it perfect for both exterior and interior applications.

BENEFITS/FEATURES

- ◆ Special formula creates an unmatched barrier between tools and the fresh concrete surface.
 - ◆ It's bubble gum scent makes this release agent pleasant to work with.
 - ◆ Evaporation and no clean-up make this product economical and easy to use.

RECOMMENDED APPLICATIONS

Antique Liquid Release is recommended for use as a bond-breaker between freshly place interior or exterior concrete surfaces and decorative texturing and stenciling tools.

TECHNICAL INFORMATION

| | |
|----------------------------------|---|
| Solids.....0% | Wet Appearance.....Clear |
| Drying Time.....1 - 2 hours | Dry Appearance.....product evaporates n/a |
| Re-Coat Time.....n/a | VOC Content.....n/a |
| Foot Traffic.....n/a | Blush Resistance.....n/a |
| Wheel Traffic.....n/a | Solvent Resistance.....n/a |
| Application Temp.....40°F - 85°F | Concrete Adhesion.....n/a |

***Please note that low air and/or concrete temperatures and/or relative humidity may extend drying times. Follow recommended coverage rates for best results.

SPECIFICATIONS/COMPLIANCES

Not Applicable.

APPROXIMATE COVERAGE RATES

| <u>Application Surface</u> | <u>First Coat</u> | <u>Optional Second Coat</u> |
|----------------------------|-------------------------|-----------------------------|
| Freshly placed concrete | 150-200 ft ² | n/a |

*Coverage rates vary depending upon surface porosity and texture, and application method.

SHELF LIFE

Antique Liquid Release has a shelf life of up to two years in it's original, sealed, unopened container.

PACKAGING

Antique Liquid Release is packaged in 1 gallon cans, 5 gallon pails, and 55 gallon drums.

SURFKOAT™

SURFACE KOATINGS, INC.

134 Davis St. Portland, TN 37148
 Phone: (615) 323-9461 Fax: (615) 323-9816
 Visit us online at: www.SurfKcoat.com

MISC. PRODUCTS

ANTIQUÉ LIQUID RELEASE

INSTRUCTIONS FOR USE

SURFACE PREPARATION: Trowel and finish freshly placed concrete surfaces to prepare for stamping or stenciling process. At the time that the concrete has reached it's "plastic" like state when texturing is mainly desired, Antique Liquid Release should be applied between the texturing tools and the freshly placed concrete surface.

Substrate temperature must be no less than 40 degrees F and not exceed 80 degrees F.

APPLICATION: Apply liberally using a solvent resistant pump-up sprayer in a mist fashion to the texturing tools to be used and the concrete surface, but only on the area where the next few texture mats or stencil will go. It is recommended to apply only over an area of about 10-20 square feet at a time to avoid evaporation of the release agent. This is especially important on cool, windy days. Continue this process until the texturing application is complete. Wash the release agent off the texturing tools simply by spraying them with water.

*Never trowel the release agent into the freshly placed concrete surface as the correct method of fixing a blemish is to use a matching texturing skin to imprint and fix that area.

**Sealing decorative concrete is imperative to a long lasting concrete surface. It is recommended to wait 28 days prior to sealing concrete to allow the entire area enough time to cure.

PLEASE NOTE: It is always recommended to test the product in a small, inconspicuous area (on the same concrete substrate) for desired results prior to application. Coverage rates may vary for all liquids/coatings and substrates depending on porosity, density, texture etc. If applying by spray method, extended coverage rates may be achieved.

CLEAN-UP

Use soap and water. Dispose of containers in accordance with local and federal regulations.

PRODUCT REMOVAL

Not Applicable.

PRECAUTIONS AND LIMITATIONS

- ▶ **Antique Liquid Release** will not freeze, however, allow temperature to rise to 50 degrees F prior to application.
- ▶ All HVAC ventilation ducts should be somehow blocked prior to application so solvents fumes are not distributed.
- ▶ Keep away from open flames. **Antique Liquid Release** is flammable and is very susceptible to ignition.
- ▶ It is not recommended to apply **Antique Liquid Release** over cured concrete as impressions can not be made.
- ▶ Coverage rates depend upon many conditions including application method, surface porosity, applicator, ect.
- ▶ **Antique Liquid Release** was designed for exterior as well as interior decorative concrete.
- ▶ **Antique Liquid Release** is not resistant to brake fluid, gasoline, and many similar products.
- ▶ It is not recommended to thin **Antique Liquid Release**.
- ▶ It is recommended to test this product prior to using on entire application..

SPECIAL NOTES

Please consult Material Safety Data Sheet (MSDS) and read Warranty information prior to use. This information can be requested by contacting customer service at 615-323-9461.

SURFKOAT™

SURFACE KOATINGS, INC.

134 Davis St. Portland, TN 37148
Phone: (615) 323-9461 Fax: (615) 323-9816
Visit us online at: www.SurfKcoat.com