









MEDIUM

911117



PVC hose with PVC rigid spiral. Used for suction and delivery of liquids, irrigation systems, and cleaning sewage drains and cesspits.

DETAILS

 SMOOTH SURFACE	****
 FLEXIBILITY	****
 ABRASION RESISTANCE	***
 TEMPERATURE RANGE	-25 °C 55 °C
 CHEMICAL RESISTANCE	PVC Table
 CRUSHING RESISTANCE	****

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	working pressure at 23 °C bar	vacuum 23 °C m/H ₂ O	bursting press. at 23 °C bar	bending radius mm	total thickness mm	Ø rigid spiral (AxB if oval) mm	spiral pitch mm	spiral direction	weight meter g/m	coil length m	Availability
51	2	50.8	61	4.5	9	13.5	200	5.1	4.8	10.5	right	960	30	On demand
63	2 1/2	63.5	75.5	4	9	12	250	6	5.5	11.3	right	1300	30	On demand
76	3	76.2	88.4	3.5	9	10.5	300	6.1	6	12.5	right	1700	30	On demand
80		80	93	3.5	9	10.5	320	6.5	6.2	14	right	1750	30	On demand
90	3 1/2	90	103.4	3	9	9	360	6.7	6.2	14	right	2150	30	On demand
102	4	101.6	116.2	3	9	9	400	7.3	6.5	14	right	2600	30	On demand
110		110.5	125.5	2.7	9	8	440	7.5	7.1	15.5	right	3000	20	On demand
120		120	136	2.5	9	7	480	8	7.3	17	right	3400	20	On demand
127	5	127	143.6	2.3	9	7	500	8.3	7.8	17.5	right	3800	20	On demand
133		133	150	2	9	6	530	8.5	8	18	right	4000	20	On demand
152	6	152.4	170.4	1.8	9	5.5	600	9	8.5	20	right	4700	20	On demand
160		160	178.8	1.5	9	4.5	650	9.4	8.5	21.5	right	5300		On demand
204	8	203.2	229.2	1.3	9	4	800	13	12	22	right	9400		On demand

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

The tolerance on all specifications ±5% (Tolerance Percentage is applicable on ALL DATA across our range)