












TERMORESISTENTE PU 200°C

912955



Hose made of polyester textile coated with PU with galvanised steel spiral embedded between two layers of textile, for suction and ducting of hot air.

DETAILS

 SMOOTH SURFACE	***
 FLEXIBILITY	****
 ABRASION RESISTANCE	*****
 TEMPERATURE RANGE	-40 °C 200 °C
 CHEMICAL RESISTANCE	PU Table
 CRUSHING RESISTANCE	***
 TEAR RESISTANCE	*****
 PERFORATION RESISTANCE	*****
 FLAME RETARDANT	Fire class M1 according to article 5 of decree of 21.11.2002 (French regulations) and UL94 VTMO class.)

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	vacuum 23 °C m/H ₂ O	bending radius mm	total thickness mm	wall thickness mm	Ø steel wire mm	spiral pitch mm	spiral direction	weight meter g/m	coil length m	Availability
40		41	45	0.98	40		0.35	1.2	14	left	185		On demand
51	2	51	56	0.95	50		0.35	1.2	14	left	225	12	In stock
63	2 1/2	64	68	0.9	60		0.35	1.2	14	left	275	12	In stock
70		71	75	0.85	70		0.35	1.2	14	left	300	12	In stock
76	3	77	81	0.8	75		0.35	1.2	14	left	320	12	In stock
83		84	88	0.75	80		0.35	1.2	14	left	360	12	In stock
89	3 1/2	90	94	0.7	90		0.35	1.2	14	left	385	12	In stock
102	4	103	107	0.65	100		0.35	1.4	16	left	480	12	In stock
114		115	119	0.55	110		0.35	1.4	16	left	540	12	In stock
121		122	126	0.5	120		0.35	1.4	16	left	580	12	In stock
127	5	128	132	0.45	125		0.35	1.4	16	left	600	12	In stock
133		134	138	0.4	130		0.35	1.4	16	left	620	12	On demand
140		141	146	0.38	140		0.35	1.4	16	left	660	12	On demand
152	6	153	158	0.35	150		0.35	1.6	18	left	780	12	In stock
178		179	184	0.25	180		0.35	1.6	18	left	920	12	In stock
203	8	204	209	0.2	200		0.35	1.6	18	left	1050	12	In stock
230		229	235	0.15	230		0.35	1.8	18	left	1350	12	In stock
254	10	255	261	0.12	250		0.35	1.8	18	left	1500	12	In stock
305	12	306	312	0.1	300		0.35	1.8	18	left	1800	6	In stock
315		318	324	0.09	315		0.35	2	22	left	1860		On demand
350		354	360	0.08	350		0.35	2	22	left	2060		On demand
400		406	412	0.06	400		0.35	2	22	left	2360		On demand

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

The tolerance on all specifications ±5% (Tolerance Percentage is applicable on ALL DATA across our range)