

AQUA 5



AGRICULTURE



Water
Discharge applications

APPLICATIONS

Water delivery lay-flat hose, for irrigation, industrial or waste water.

TECHNICAL DESCRIPTION

Inner tube: SBR, black, smooth.

Reinforcement: synthetic textile.


Cover: SBR, black, fabric impression.

Temperature range: -30°C to +80°C.



TRELLEBORG

AQUA 5





AGRICULTURE

AQUA 5



ID mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK () or min. order m
51.0	59.0 ±1	5	15	0.94	40	5503670	
76.0	84.0 ±1	5	15	1.41	40	5503672	
90.0	98.0 ±1	5	15	1.69	40	5503673	
102.0	110.0 ±1	5	15	1.86	40	5503664	
152.0	161.0 ±1	5	15	3.19	40	5503666	
203.0	213.0 ±1	5	15	4.22	40	5503667	
254.0	264.0 ±1	5	15	5.28	40	5503668	
305.0	316.0 ±1	5	15	6.81	40	5503669	

Tolerance on length: ±1% (ISO 1307 Standard).



TRELLEBORG

WWW.TRELLEBORG.COM/FLUIDHANDLING