

# T877


## SFUCEM 40N

Dorngefertigter Zementsiloschlauch geeignet zum Durchleiten von Zement, Kalk, Kies und pulverförmigen abrasiven Medien mit kleiner Teilchengröße. Geeignet auch für Tanklastwagen


Mandrel built bulk material delivery hose suitable for abrasive materials such as cement, chalk, lime and abrasive powders with small granules. Suitable for silo discharging and on tank trucks.



### Technische Daten

<b>Seele</b>	Schwarzes, glattes Gummi, abriebfest
<b>Einlagen</b>	Synthetische Textileinlagen.
<b>Decke</b>	Schwarzes, glattes Gummi, abrieb- und witterungsbeständig. Stoffgemustert.
<b>Betriebsdruck</b>	6 bar
<b>Soll-Platzdruck</b>	18 bar
<b>Temperatur</b>	-40 °C +70 °C
<b>Markierung</b>	 BULK MATERIAL DELIVERY W.P. 6 BAR – 85 PSI (in orangener Schrift)

### Technical Characteristics

<b>Tube</b>	Black smooth rubber, resistant to abrasion.
<b>Reinforcement</b>	High tensile textile plies.
<b>Cover</b>	Black, smooth, weather and abrasion resistant rubber. Fabric impression.
<b>Working Pressure</b>	6 bar
<b>Nominal Burst Pressure</b>	18 bar
<b>Temperature</b>	-40 °C +70 °C
<b>Marking</b>	 BULK MATERIAL DELIVERY W.P. 6 BAR 85 PSI (in orange letters)

### Abmessungen / Sizes

Innendurchmesser Inner Diameter	Wanddicke Wall Thickness	Außendurchmesser Outside Diameter	Seele Tube	Gewicht Weight
mm	mm	mm	mm	Kg/m
102	5	112	2,5	1,93