

## DUAL TECH CEILING MOUNT MOTION SENSOR



### SPECIFICATIONS

Input Voltage: AC120-277V  
 Frequency: 60Hz  
 Input Current: 10 Amp  
 Input Power: 720-1662W  
 Output Voltage: AC120-277V  
 Output Current: 10 Amp  
 Output Power: 720-1662W  
 Dimming: Class 2, 0-10V DC 10mA Max  
 Sinking Current: 10mA Max

Bluetooth Transmit: 200ft Max  
 Radio Frequency: 2.4GHz ± 75MHz  
 Bluetooth Version: 4.2  
 Housing Material: UL 94-5VA,  
 Indoor Use Only  
 Operating Temperature: -30°C to 65°C,  
 -22°F to 149°F  
 Storage Temperature: -30°C to 85°C,  
 -22°F to 185°F  
 IP Rating: IP20  
 Color: White  
 Warranty: Limited Lifetime

Comply to UL8750, UL2043, UL1376, RoHS  
 Safety: cULus Listed LED Controller  
 E504054  
 FCC ID: 2A26YLTKTVT2021  
 DID: D057145  
 DLC: NLTRC5KL0TN

### FEATURES

The SMRT DT-WH-BT is a sleek, powerful dual technology ceiling mount motion sensor that runs on the SMRT Bluetooth network based system. The sensor utilizes reliable Passive Infrared (PIR), and Ultrasonic technologies, providing the highest level of reliability, accuracy and coverage. The sensor can be set to Occupancy, which auto detects motion to trigger the lights to an on state, and then will time out and turn the lights off when there is no motion present. It can also be set to Vacancy, which requires turning the lights on with a wall switch, and then will time out and turn the lights off when there is no motion present. The sensor can be configured in our free Bluetooth app.

### DIMENSIONS / WIRING / DETAILS

Unit: inch/mm

