



MJM INTERNATIONAL CORPORATION

418-OR-3TW


WARNING NOT SECURING ALL PARTS PROPERLY CAN CREATE A SERIOUS SAFETY HAZARD.

IDENTIFY ALL COMPONENTS TO START ASSEMBLY

PARTS INCLUDED FOR WALKER


- ☐ PARTIALLY ASSEMBLED FRAME.
- ☐ 4 CASTERS (2 WITH BRAKE & 2 NON BRAKE)
- ☐ SIDE OUTRIGGERS WITH ANTI-TIPS--2
- ☐ SIDE RAILS--- 2 MAKE UP THE ARM SECTIONS
- ☐ SPRING LOADED FLAT GATE---1 IS CONNECTED TO ONE SIDE RAIL
- ☐ PVC BACK --1
- ☐ MESH SLING-- 1
- ☐ SEAT CUSHION--1
- ☐ SAFETY BELT-- 1
- ☐ CLAMP LOCKS FOR ADJUSTABLE HEIGHTS--- 4 PLACED ON BOTTOM FRAME
- ☐ REINFORCEMENT RINGS -- 4 ATTACHED TO BOTTOM FRAME IN CORNERS

STEP 1



NOTE: A PHILLIPS SCREWDRIVER OR A CORDLESS HAND DRILL IS REQUIRED TO TIGHTEN/SECURE ALL SCREWS.

STEP 2




REMOVE SCREWS FROM REINFORCEMENT RINGS

STEP 3



INSERT CASTERS --PLACE BRAKE WHEELS ON THE REAR OF THE WALKER

STEP 4



SECURE CASTERS WITH SCREWS PROVIDED USING PILOT HOLE AS REFERENCE

STEP 5



INSERT OUTRIGGERS ON THE SIDE OF THE BOTTOM FRAME BY MATCHING COLOR CODED DOTS AND SECURE USING SCREWS PROVIDED USING PILOT HOLES AS REFERENCE

STEP 6



REMOVE SCREWS FROM AREA BY SEAT SECTION

STEP 7-1



INSERT SIDE RAILS BY MATCHING COLOR CODED DOTS.



MJM INTERNATIONAL CORPORATION

418-OR-3TW


WARNING NOT SECURING ALL PARTS PROPERLY CAN CREATE A SERIOUS SAFETY HAZARD.

STEP 7-2



INSERT SIDE RAILS BY MATCHING COLOR CODED DOTS .

STEP 7-3




SECURE SIDE RAILS USING SCREWS PROVIDED AND PILOT HOLES AS REFERENCE

STEP 8



INSERT MESH SLING WITH PVC BACK TOWARDS SEAT SECTION ON TOP OF SIDE RAILS, SECURE USING SCREWS PROVIDED AND PILOT HOLES AS REFERENCE.

STEP 9



ADJUST MESH SLING AS NEEDED

STEP 10



SECURE FLAT GATE ON FRONT SIDE RAIL USING PILOT HOLE PROVIDED

STEP 11



418-OR-3TW COMPLETELY ASSEMBLED

NOTE: CLAMP LOCKS CAN BE REMOVED TO ADJUST THE HEIGHTS ON THE WALKER.

NOTE: SECURE SAFETY BELT ON THE FRONT GATE AND SECURE SEAT CUSHION WITH VELCRO

NOTE: CASTERS/CLAMP LOCKING SYSTEM MUST BE CHECKED AND SECURED PRIOR TO USING 418-OR-3TW

MJM International Corporation
www.mjminternational.com

1-800-270-6199

Fax: (956) 781-5552
hmorales@yahoo.com