

5.5HP Belt Driven Screw Compressor

Features & Benefits

- Genuine 4KW / 5.5HP Three Phase Motor
- High Pressure for truck tyre inflation
- Certified & registered Pressure Vessel to AS1210
- Schneider Electrical components
- Ease of access with service panels
- Certified safety valve
- Audible and Visual alarm
- 110L Air Receiver with pallet feet
- Super quiet running noise at 62dB(a) (+/- 2)
- 99% Duty Cycle
- LED Control Panel
- Australian owned & local manufacturer
- Emergency stop button
- Servicing schedule based upon run hours
- Every air compressor extensively tested and signed off by a Peerless Specialist



195KG



1100MM X 530MM X 1230MM



WARRANTY
1 YEAR TOTAL UNIT



TARGET MARKETS

- DAIRY INDUSTRY
- DENTISTS
- AUTOMOTIVE INDUSTRIES
- TYRE SHOPS
- PANEL BEATERS
- SPRAY PAINTERS
- FOOD PACKAGING
- MARINE INDUSTRIES
- AGRICULTURAL SECTOR

Product Description

The High pressure 5.5HP screw is finally here, giving an impressive 500 litres of free air delivery at 116PSI (8BAR). If you have a small tyre shop that requires truck tyre inflation, this is the air compressor for you!

Belt driven by a 5.5HP motor with an oil injected airoend allowing a 99% duty cycle means you can run this air compressor continuously unlike piston air compressors that demand a duty cycle.

Suited for the industrial workshop (1-2 man) wanting that greater air flow that allows for a constant demand.

The overall size of the air compressor is also impressive, fitted on top of a 110L tank measuring at 1100MM X 530MM X 1230MM. This makes it one of the most compact air compressors. When in operation it is also very quiet which is a massive feature in smaller workshops.

The electronic controller will operate the machine and show you all the information you need with live feedback. The controller will also show you the service intervals and alarm when a service is required. This is critical to keeping your air compressor in top shape.

Being only 5.5HP this machine has a small AMP draw making it perfect for smaller shops where a larger screw isn't needed.

If you require any further information or advice, contact Peerless Products on 03 5434 4200.

SPECIFICATIONS

CODE	HP / KW	COMPRESSOR TYPE	PRESSURE	FLOW RATE			AIR OUTLET THREAD	TANK (L)
				LPM	M ³ /H	CFM		
HQB5.5HP	5.5 HP / 4 KW	OIL LUBRICATED SCREW	8 BAR / 145 PSI (MAX 10BAR)	500	30	17.7	1/2" BSP	110L