





SUNHAN TECHNOLOGY LIMITED

E-mail:info@sunhanpack.com Whatsapp:0086 135 6037 4877

SUNHΛN **DRIVING FORCE OF A COMPLETE** PACKAGING SOLUTION

Filling Machine Filler & Capper Filler & Sealer



been committed to the packaging system, including R&D, manufacturing, and sales since 2014. It is a domestic professional company engaged in the food and daily chemical industries. It is a high-tech and modern enterprise with a number of national patent certificates. The company's plant is about 6,800. It mainly develops and produces a series of packaging equipment such as filling machines, capping machines, labeling machines, coding machines, sealing machines, etc., to provide customers with one-stop supply and technical solutions. At present, the products have been exported to more than 100 countries and regions around the world, and are well-recognized by domestic and foreign customers.



ABOUT US

SUNHAN has



HISTORY

SUNHAN RAK





The company operates 3 ubsidiaries with a total area of over 6800 sqm and a staff of 95. It has earned an ISO9001 certificate, reaching the international quality and management standard.





SUNHAN

Now **SUNHAN** is aiming to become one of China's hightech enterprises and a model enterprise in the packaging industry.

4 Heads Automatic Liquid Filling Machine

This desktop automatic machine is with high cost performance. It is widely used to fill essential oils, perfumes, juice various industries like beverage, daily chemical and comestics. Filling machine with magnetic pump is a good choice for low viscous, weakly corrosive liquid.

- 1. Multiple filling nozzles can be customized as production need.
- 2. 6L/7.5L/9L/12L magnetic pump can be chosen according to filling volume.
- 3. Diving nozzles can be customized according to filling material.
- 4. Equipped with 316 stainless steel magnetic pump, it is suitable for weakly corrosive liquid.

| Machine model | SH-DTMP4A | |
|----------------------------------|--|--|
| Power supply | 110/220V 50-60HZ | |
| Maximum flow rate | 6L/min 7.5L/min 9L/min 12L/min can be chosen | |
| Working speed | 20-40 bottles/min(based on liquid and filing volume) | |
| Air pressure | 0.3–0.4MPa | |
| Flling accuracy | ≤+1% (Based on water) | |
| Diameter of Flling Nozzle | 6/8mm | |
| Delay Range | 0.01–999.9s | |
| Count Range | 1-99999 Times | |
| Filling Volume | 3-1000m(220V)3-500ml(110V) | |
| Size of air compressor connector | OD 8mm | |
| Suitable bottle height | <220mm(Can be customized,max height 300mm) | |
| Package Size:About | 1110*650*420mm | |



Peristaltic pump filling machine

This automatic machine is in small desktop design, it saves working space and can work with desktop capping/labeling machine. It is widely used to fill essential oils, perfumes, juice various industries like beverage, daily chemical and comestics.

- 1. Multiple filling nozzles can be customized as production need.
- 2. 2.5L/4L/6L/12L peristaltic pump can be chosen according to filling volume.
- 3. Diving nozzles can be customized according to filling material.
- 4. The liquid will not pass through the pump.

| Machine model | SH-D |
|---------------------------|-----------------------|
| Filling nozzle | |
| Machine Voltage | AC110V/220 |
| Machine Power | 60W(Ea |
| Recommended filing volume | 110V 10-500ml |
| Maximum flow rate | 2500m/min for each n |
| Filling nozzles | 4(2/6/8 nozzles of |
| Working speed | 30-50 bttles/min(base |
| Air pressure | 0.3-0 |
| Filling accuracy | ≤ <u>±</u> 1%(|
| Dimension of fling nozzle | standard 8n |
| Delay range | 0.01s - |
| Belt length | 1. |
| Suitable bottle height | <220mm(Can be custom |
| | |



as production need. chosen according to filling volume. ng to filling material.

DTPP4B

- 4
- 0V 50Hz-60Hz
- ach Pump)
- 220V 10-1000ml
- nozzle (based on water
- can be customized)
- ed on bottles and liquids)
- 0.4mpa
- for water) mm and 6mm
- 999.9s
- 999. 0---
- .0m
- mized,max height 300mm)



Chain Conveyor Liquid Filling Machine

The chain conveyor belt filling machine has larger weight capacity, this is possible to fill large volume products, it can transfer bottles more smoonthly.

- 1. Multiple filling nozzles can be customized as production need.
- 2. 4L/12L diaphragm pump can be chosen according to filling volume.
- 3. Diving nozzles can be customized according to filling material.

| Machine model | SH-DTDP-4P |
|----------------------------------|---|
| Voltage | 110/220V 50-60HZ |
| Power | 250W |
| Maximum flow velocity | 4000ml/min(Each nozzle and base on water) |
| Working speed | 1500–3000 bottles/hour(depends on bottle size and liquid) |
| Air pressure | 0.3–0.4MPa |
| Filling accuracy | ≤+1% (For water) |
| Bottle height | <220mm(Can be customized,max height 300mm) |
| Diameter of filling nozzle | 6/8mm |
| Conveyor size | 1030*115mm(L*W) |
| Size of air compressor connector | OD 8mm |
| Machine size | 1114*650*765mm |
| Machine weight | 52kg |



Tabletop Automatic Bottle Liquid Filling Machine

Reasonable desktop design saves working space. Chain conveyor belt has large weight capacity to transfer heavier products smoothly. It is widely used in food, daily chemical, advanced comstics industries.

- 1. Multiple filling nozzles can be customized as production need.
- 2. 6L/7.5L/9L/12L magnetic pump can be chosen according to filling volume.
- 3. Diving nozzles can be customized according to filling material.
- 4. Equipped with 316 stainless steel magnetic pump, it is suitable for weakly corrosive liquid.

| Machine model | SH-D |
|----------------------------------|-----------------------|
| Power supply | 110/220V 50 |
| Maximum flow velocity | 6000ml/min (Each noz: |
| Working speed | 20–30 b |
| Air pressure | 0.3–0 |
| Filling accuracy | ≤±1%(1 |
| Dimension of filling nozzle | Standard 8r |
| Delay range | 0.01s- |
| Count range | 1–9999 |
| Size of air compressor connector | OD 6 |
| Package size | About 1150 |
| Net weight/Gross weigh | About 5 |
| | |



as production need. chosen according to filling volume. ng to filling material. c pump.it is suitable for weakly corrosiv

DTMP4Y

- 50-60HZ 300W
- zzle and based on water
- oottles/min
- 0.4mpa
- for water)
- mm and 6mm
- -999.9s
- 99 times
- 6/8mm
-)*650*820mm
- 59kg/89kg







FILLING MACHINE

Tabletop Automatic **Bottle Liquid Filling Machine**

Desktop full automatic machine is very efficient with high cost performance. It is widely used in medicine, daily chemical and other industries such as essential oils, perfumes, juice liquid etc. Machine with peristaltic pump is easy to change tube. Liquid won't pass through the pump. Ensue the cleanliness of the liquid.

- 1. Multiple filling heads can be customized.
- 2. Diving nozzle can be customized for foamy liquid.
- 3. 2.5L/4L/6L/12L peristaltic pump can be chosen according to filling volume.

| Machine model | SH-DTPP4C |
|----------------------------------|---|
| Power supply | AC110V/220V 50Hz-60Hz 60W(Each Pump) |
| Filling Range | 2500ml/min |
| Maximum flow | 2500m/min for each nozzle (based on water) |
| Filling nozzles | 4(we can customize the nozzles based on your demands) |
| Working speed | 30-50 bottles/min(based on bottles and liquids) |
| Air pressure | 0.3-0.4MPa |
| Filling accuracy | ≤±1% (For water) |
| Diameter of filling nozzle | 6/8mm |
| Delay range | 0.01-999.9s |
| Belt length | 1m |
| Size of air compressor connector | OD8mm |



The 6 nozzle peristaltic pump is designed with automatic conveyor belt to realize automated production. It is suitable for small volume liquid like eye drops, essential oil. Each nozzle of this machine can be controlled separately. The peristaltic pump can ensure the liquid cleaness and filling accuracy.

- 1. Multiple filling nozzles can be customized as production need.
- 2. Diving nozzles can be customized according to filling material.
- 3. Nylon peristaltic pump can be customized for heat liquid.

| Machine model | SH-D |
|----------------------------|---------------------------|
| Power supply | AC110V/220V 5 |
| Filling Range | ≤5 |
| Maximum flow | 650ml/min for each n |
| Filling nozzles | 6(we can customize nozzle |
| Working speed | 40–50bottles/min(b |
| Filling accuracy | ≤±1% (F |
| Diameter of filling nozzle | 4r |
| Delay range | 0.01- |
| Conveyor size | 1080*350 |
| Machine size | About 320*440*300mm |
| Net weight | Abou |
| | |





Nozzle Liquid Filling Machine

DTPP6B

- 50Hz-60Hz 60W*6
- 50ml
- nozzle (based on water)
- les based on your demands)
- based on 50ml-water
- For water
- mm
- -999.9s
- 50mm(L*W)
- m(Without conveyor belt)
- ut 31kg

Ζ G Ζ $\mathbf{\Sigma}$ \mathbf{O} I _ Ζ

Desktop Automatic Paste Filling Machine

This desktop filling machine is equipped with rotor pump which is good for filling thick liquid or paste like pepper sauce,tomato paste,curry paste,jam.It can filling material accurately and automatically,helps you improve working efficiency.It is widely used in food,daily chemical and cosmetics industries.

- 1. Mixing and heating function can be customized as production need.
- 2. Chain conveyor belt can be customized.
- 3. Equipped with rotor pump, it has 5–5000ml large filling range, it can fill paste accurately.

| Machine model | SH-DTGT900 |
|--------------------------|--------------------------------------|
| Machine power | 840W |
| Recommend filling volume | 5–5000ml |
| Filling accuracy | ≤±1% |
| Bottle opening size | φ>20mm |
| Hopper size | 30L |
| Working speed | 10-60bottles/min(based on 250ml jam) |
| Machine size | About 1090*700*680mm |
| Machine weight | About 54kg |
| | |



Tabletop Automatic Liquid Filling Machine

This desktop filling machine is equipped with chain conveyor belt, compared with the leather conveyor belt, this one is with larger capacity, this makes it suitable for filling larger volume and transport them faster and more smooth. The magnetic pump filling machine is high precision that it can be used to fill essential oil, solution, eye drops, inks, perfume etc.

- 1. Multiple filling nozzles can be customized as production need.
- 2. Equipped with stainless steel pump, it fills liquid accurately.
- 3. It can work with automatic capping/labeling machine to realize automated production.

| SH-D |
|-------------------------|
| 220V/110V 5 |
| 316L Stainless St |
| 5–10 |
| 4 Heads(We can cu |
| 20-30bottles/min(depend |
| 3200ml/min(Each nozz |
| H: 100- |
| 1200mm*1 |
| OD 6 |
| 0.01- |
| ±0 |
| OD |
| About 1200 |
| |



as production need. iquid accurately. ng machine to realize automated production

DTMP4C 50–60Hz 400W teel Magnetic Pump 000mL customize 2/6 heads) d on material and bottle size) zle and depend on water) D–200mm 100mm(L*W) 6/8mm –999.9s 0.5%

0*700*850mm

FILLING MACHINE

Desktop Automatic 4 Heads **Paste Filling Machine**

Designed for filling paste or thick liquid, this machine can work with desktop capping machine and labeling machine to save your working space and improve your production efficiency. Each nozzle of this machine can be controlled separately, we can customize multiple filling nozzles as your production need. This machine is widely used in food, daily chemical, cosmetics industries.

- 1. Multiple filling nozzles can be customized as production need.
- 2. Different filling range can be chosen according to filling volume.
- 3. Suitable for thick liquid like shampoo & lotion.
- 4. Extra mixing and heating function can be customized.

| Machine model | SH-DTGT4T |
|---------------------|--|
| Power | 110/220V 50-60HZ About 300W |
| Filling nozzle | 4 Heads(We can customize 2/6 heads) |
| Filling range | 10-100ml/30-300ml/50-500ml/100-1000ml/500-2500ml/1000-5000ml |
| Working speed | 20–30bottles/min(based on liquid&filling volume) |
| Hopper size | 90L |
| Conveyor size | About 1300*100mm |
| Filling nozzle size | OD 10mm(can choose other size) |
| Filling accuracy | ≤±1% |
| Machine size | About 1300*1440*1200 mm |
| Package size | About 1550*1400*1330mm |
| Package weight | About 237kg |
| | |









Desktop Automatic Vacuum **Liquid Filling Machine**

When filling nozzle inserted into an empty bottle, the seal rings will help to seal bottle and the air in the bottle will be pulled out by vacuum pump. The vacuum in the bottle then sucks liquid into the bottle. When the bottle is full and reaches the preset filling level, the extra liquid will be transferred back to the storage tank, and the bottle will keep full.

- 1. Multiple filling nozzes can be customized
- 2. Vacuum filling, it is can keep the fragrance during filling work
- 3. Desktop type design saves working space
- 4. Product is filled without any contact between product and pumps or mechanical components.

| SH-DTZL500 |
|------------------------|
| About 80W |
| About 5–500ml |
| 20–40 bottles/min (4 r |
| 0.4-0.8MPa |
| <200mm |
| <22mm |
| About 30mm |
| <100mm |
| About 117*69*118 |
| 71kg |
| 1100*580*1090m |
| About 107kg |
| |









77 Ζ G Ζ \mathbf{D} \mathbf{O} Т Ζ m

Desktop Automatic **Powder Filling Machine**

This small auger filling machine is suitable for filling milk powders, flour, fodder into bags or bottles. It is easy to operate and can fill powder accurately. This machine is widely used in food, cosmetic and daily chemical industries.

- 1. Desktop type filling machine which help you saveworking space.
- 2. Filling nozzle size can be customized according to production need.
- 3. Can work with automatic capping and labelingmachine to realize automated production.

| Machine model | SH-FM3A |
|---------------------|--------------------------|
| Voltage | 110/220V |
| Machine power | 0.5KW |
| Hopper size | About 6L |
| Hopper diameter | About 320mm |
| Filling range | 50-500g |
| Filling nozzle size | 20mm (Can be Customized) |
| Filling accuracy | a±1% |
| Filling speed | About 10 bottles/min |
| Working height | 420-490mm(Adjustable) |
| Conveyor length | About 1100mm |
| Conveyor width | About 140mm |
| | |



Full Automatic Magentic **Pump Filling Machine**

This automatic filling machine is equipped with magnetic pump, which can ensure the filling accuracy. The filling speed of each nozzle can be controlled separately. It has compact design, beautiful appearance, wide application field, and it works with imported parts, so that the the machine has a good performance. This machine is suitable for filling essential oil, eye drops, ink etc.

- 1. Multiple filling heads can be customized.
- 2. 4L/6L/7.5L/9L/12L magnetic pump can be chosen.
- 3. Dust cover is optional for improving production quality.
- 4. Diving nozzle is good for foamy liquid.

| Machine model | SH-V1 |
|----------------------------------|------------------------------|
| Voltage | 220V-50HZ |
| Machine power | 20 |
| Container size | ф20–160mm |
| Max flow rate | 6000ml/min/7500r |
| Material of pump | 316stair |
| Filling accuracy | ≤100ml deviation≤±1ml > 100m |
| Filling speed | 20-50pcs/min(depending |
| Size of air compressor connector | OD |
| Packing weight | About |
| Packing size | About 2000* |
| | |



TMP80C Z/110V-60HZ W000 n H30–300mm ml/min/12000ml/min nless steel nl deviation≤±1% (based on water) on bottles and filling liquid) 08mm ıt 150ka *820*1580mm

> _ Ζ G Ξ $\mathbf{\Sigma}$ C Т Ζ

SUNH^N

Full Automatic Peristaltic pump Filling Machine

Equipped with peristaltic pump, this liquid filling machine can work automatically, it can fill about 30–50 bottles/min. Each filling nozzle of this machine can be controlled separately, additionally the liquid will not pass through the pump during filling, ensure the liquid is clean after filling.

- 1. Multiple filling heads can be customized.
- 2. Diving nozzle is good for foamy liquid.
- 3. 2.5L/4L/6L/12L peristaltic pump can be chosen according to filling volume.
- 4. Dust cover is optional for improving production quality.

| Machine model | SH-VTPP80C |
|------------------|---|
| Power supply | 220V-50HZ/110V-60HZ |
| The pump power | 60W(For Each Nozzle) |
| Filling pump | Peristaltic Pump |
| Container size | ф 20–160mm Н 30–300mm |
| Filling range | 3-4000ml(We also have 3-2500ml and 10-12000ml) |
| Max flow rate | 4000m/min for each nozzle(based on water) |
| Filling accuracy | ≤ \pm 1%(for water) |
| Filling speed | 30-50 bottles/ min(depending on bottles and filling liquid) |
| Packing size | 2030*820*1570mm |
| Packing weight | 150Kg |
| | |



Full Automatic Diaphragm Pump Filling Machine

Equipped with diaphragm pump, this liquid filling machine can work automatically, it can fill about 30–45 bottles/min. Each filling nozzle of this machine can be controlled separately, additionally the 40L/min large flow rate makes it suitable for fill thicker liquid like gel, hand sanitizer, laundry detergent, shampoo etc.

- 1. Multiple filling heads can be customized.
- 2. Diving nozzle is good for foamy liquid.
- 3. 4L/12L/40L diaphragm pump can be chosen according to filling volume.
- 4. Dust cover is optional for improving production quality.

| Machine model | SH-V1 |
|----------------------------------|-------------------------------|
| Power supply | 220V-50HZ/ |
| The whole machine power | 150 |
| Max flow rate | 50ML/min |
| Material of pump | Diaphrag |
| Size of air compressor connector | OD8 |
| Filling accuracy | ≤100ml deviation≤±1ml > 100ml |
| Filling speed | 30-45bottles/min(depending |
| Packing size | About1920*1 |
| Packing weight | About |
| | |



sen according to filling volume. ction quality.

/TDP40 Z/110V–60HZ 500W in–40L/min agm Pump 98mm nl deviation≤±1% (based on water) ng on bottles and filling liquid) 1110*1800mm t 150kg

FILLING MACHINE

Automatic Vacuum Liquid **Filling Machine**

The vacuum liquid filling machine can prevent the fragrance of liquid from spreading, this is especially good for perfume filling. It is full automatic and can work with automatic capping machine to realize automated production. Multiple filling nozzles can be customized according to production needs.

- 1. Multiple filling nozzes can be customized.
- 2. Dust cover is optional for improving production quality.
- 3. It can work wth automatic capping/labeling machine to realize full automated prduction.

| Machine model | SH-YTZL4A |
|-------------------------|--|
| Filling head | 4 Head |
| Air pressure | 0.5-0.8MPa |
| Liquid level accuracy | ±1mm |
| Viscosity range | The maximum applicable viscosity is 20Cps (static viscosity) |
| Working Speed | 20-40 Bottles/Minute |
| Bottle height | ≤250mm |
| Bottle Opening Size | ≤φ4.5mm–φ28mm |
| Adjustable liquid level | 15–50mm |
| Pumping rate | 5.5L/S |
| Machine size | About 1500*1150*1530mm |
| Machine weight | About 278kg |
| Package size | About 1660*1310*1670mm |
| Package weight | About 339kg |
| | |



Automatic Rotor Pump Filling Machine With Rotary Plate

This machine is equipped with high quality rotor pump which can filling paste faster and more accurately. The rotary plate can make bottles be in order before filling work and transport the finished products. This machine is widely used in food, daily chemicaly and cosmetics industries.

- 1. Mixing and heating function can be customized as production need.
- 3. Suitable for filling small filling volume paste.
- 4. Enter certain number to set filling volume, quantitative filling simplify adjustment process.

| Machine model | SH-V |
|----------------------|--------------------------------|
| Machine voltage | 110/220V 50 |
| Filling pump | Rotor |
| Filling range | About 5- |
| Suitable bottle size | φ=50–100mm |
| Hopper size | Abou |
| Working speed | 20-35 bottles/min(based on fil |
| Working height | About 85 |
| Machine size | About 1688*1 |
| Machine weight | About |



2. Equipped with rotor pump, it has 5–5000ml large filling range, it can fill paste accurately.

VTRP1 50-60HZ 1KW nump –5000ml H=50-250mm ut 25L illing material and filling volume) 50±25mm 1204*1800mm 200ka

_ Ζ G \leq \mathbf{D} \mathbf{O} Т _ Ζ

Automatic Rotor Pump Paste **Filling Machine**

This machine is equipped with high quality rotor pump which can filling paste faster and more accurately. It can work with automatic capping and labeling machine to realize automated production. This machine is widely used in food, daily chemicaly and cosmetics industries.

- 1. Mixing and heating function can be customized as production need.
- 2. Equipped with rotor pump, it has 5-5000ml large filling range, it can fill paste accurately.
- 3. Suitable for filling small filling volume paste.
- 4. 4. Enter certain number to set filling volume, quantitative filling simplify adjustment process.

| Machine model | SH-VTRP1A |
|--------------------------|--|
| Voltage | 220V/110V 50-60Hz |
| Power | About 230W |
| Machine Pump | Rotor Pump |
| Minimum Filling Range | 50–1500ml |
| Filling Speed | About 25 bottles/min(based on 500ml water,depends on bottle size and liquid) |
| Filling Accuracy | ≤±1% |
| Filling Nozzle Diameter | OD 25mm |
| Suitable Bottle Height | 30mm-235mm |
| Suitable Bottle Diameter | 30mm–110mm |
| Hopper Capacity | About 30L |
| Machine Size | About 1880*760*1510mm |
| Machine Weight | About 95kg |



4 **Heads Automatic Filling Machine**

This paste filling machine is designed for filling paste like curry paste, tomato sauce, pepper sauce, each nozzle can be controlled separately, the filling range and speed are adjustable according to operation. This machine can work with capping machine and labeling machine to realize automated production.

- 1. Multiple filling heads can be customized as production need.
- 2. Diferent filling range can be chosen.
- 3. Extra mixing and heating function can be realized.
- 4. Dust cover is optional for improving production quality.

| Machine model | SH-YT |
|----------------------------------|------------------------------|
| Voltage | 110/220V 50 |
| Filling Range | 5-100m/10-300ml/50-500ml/100 |
| Filling Nozzle | 4 heads(we can custo |
| Working Speed(based on water) | 20- 50bc |
| Filling Accuracy | ≤+ |
| Air Pressure | 0.5–0 |
| Conveyor Size | About 1990 |
| Size Of Filling Nozzle | φ10 |
| Size Of Air Compressor Connector | φ10 |
| Machine Weight | 26 |
| Dimension | 200x120 |
| | |



′T4T-4P

50-60HZ 800W 0-1000ml/500-3000m/1000-5000ml tomize 2/6/8/12 heads) oottles/min +1% 0.7MPa 0*100mm(l*w) 0mm 0mm 30kg 20x230cn

Ζ G Ξ \mathbf{D} \mathbf{O} T _ Ζ

Automatic **Filling Machine**

This automatic filling machine is with larger air cylinder which can help to fill liquid faster. This machine is easy to operate and each nozzle can be controlled separately, it can work with the capping machine, labeling machine to achieve to automatic production line, helps you improve working efficiency.

- 1. Multiple filling nozzles can be customized according to production need.
- 2. Different filling range can be chosen.
- 3. Dust cover can be customized for improving production quality.

| Machine model | SH-YT6T-6Y |
|----------------------------------|--|
| Voltage | 110/220v 50-60hz 800w |
| Filling Range | 5-100ml/10-300m/50-500ml/100-1000ml/500-3000ml/1000-5000ml |
| Filling Nozzle | 6 Heads(We Can Customize 2/4/8/12 Heads) |
| Working Speed(Based On Water) | 10-30botles/Min:20-35bottles/Min:30-40bottles/Min:35-45bottles/Min |
| Filling Accuracy | ≤±1% |
| Air Pressure | 0.5-0.7mpa |
| Conveyor Length | 2050mm(Standard)/3050mm(Custom Version) |
| Conveyor Material | Plastic (Standard)/Stainless Steel (Custom Version) |
| Size Of Air Compressor Connector | Od 10mm |
| Machine Weight | 300kg |
| Power Of Whole Machine | 800w |
| Dimension | 3200x860x1460mm |



Servo Motor Automatic **Filling Machine**

Compared with other piston pump filling machine, this one is controlled by servo motor, and operator just need to enter certain number to control filling volume, this is more convenient and easier to operate. This machine is good for filling paste and liquid, includes hot sauce,ketchup,honey,lotion.

- 1. Enter certain number to set filling volume, easy to adjust machine.
- 2. Multiple filling nozzles can be customized.
- 3. It can work with automatic capping/labeling machine to realize automated production.

| Machine model | SH-GY1SM |
|----------------------------|---|
| Voltage supply | 220/110V 50/60Hz |
| Power | 900w |
| Filling accuracy | ≤±0.5% |
| Filling speed | 10–25 bottles/min |
| Filling volume | 5-100/10-300/50-500/100-1000ml(choose based on your requirement) |
| Conveyor size | 2m*10cm(L*W) |
| Equipped with air pressure | 0.4-0.6 MPa |
| Air consumption | ≥0.1m ³ /min |
| Machine weight | 82kg(Filling machine)+36kg(Conveyor belt) |
| Package weight | 108kg(Filling machine)+59kg(Conveyor belt) |
| Package size | 65*70*132cm(Filling machine)+45*45*48cm(Hopper)209*45*50cm(Conveyor belt) |



П Ζ G Ζ \mathbf{D} \mathbf{O} Т Ζ

SUNHΛN

4 Heads Servo Filling Machine

The servo filling machine can be used to fill liquid or paste by entering certain filling range. It will be more accurate and easier to operate, it will not fill liquid if no bottle pass through. This machine is equipped with piston pump, widely used in various industries such as daily chemical, food, medicine, cosmetics and so on.

- 1. Enter certain number to set filling volume, easy to adjust machine.
- 2. Multiple filling nozzles can be customized.
- 3. Different filling range can be chosen according to filling volume.

| Machine model | SH-SV4G |
|----------------------------------|---|
| Voltage | 110-60HZ 220V-50HZ |
| Power | 1500W |
| Air consumption | 0.4-0.6MPa |
| Filling accuracy | ±1% |
| Filling Nozzle | 4 heads(we can customize 2/6/8/12 heads) |
| Working speed | 20-50 bottles/min(based on material) |
| Size of filing nozzle | ф10mm |
| Size of air compressor connector | φ10mm |
| Filling range | 10-100ml/30-300ml/50-500ml/100-1000ml/500-3000m/1000-5000ml |
| Machine size | About 2500*1370*2070mm |
| Machine weight | About 549.5kg |
| Package size | About 2105*1450*2300mm |
| Package weight | About 650.5kg |
| | |



Automatic Powder Filling Machine

This powder filling machine is widely used to fill powder products like amber powder, diatomite powder, milk powder, matcha powder. This machine gets a lot of popularity from manufactures come from food, cosmetics, pharmaceutical industries.

- 1. Filling volume is controlled by auger.it can ensure the filling accuracy.
- 2. Filling nozzle size can be customized according to bottle size.
- 3. It can work with automatic capping, labeling machine to realize automted production.

| Machine model | SH-FM1A |
|--------------------------|----------------------------------|
| Voltage | 220V/110V |
| Power | 500W |
| Filling speed | 10–15pcs/min (based on material) |
| Suitable bottle diameter | Less than 100mm |
| Applicable bottle height | Customized |
| Filling heads | Only one |
| Filling material | Powder |
| Package size | 230*150*240cm |
| Package weight | About 400kgs |
| | |



ensure the filling accuracy. rding to bottle size. g machine to realize automted production.

FILLING MACHINE

Automatic Granule **Filling Machine**

The measuring cup type automatic granule packaging machine can only pack granular powder with high density and non-viscous, and is not suitable for granular with low density and lightness or viscosity. The machine is suitable for industries such as food, daily chemicals, and agriculture.

- 1. Filling nozzle size can be customized according to bottle size.
- 2. It can work with automatic capping, labeling machine to realize automted production. 3. Filling volume is controlled by measuring cup.it can ensure the filling accuracy of
- each bottles.

| Machine model | SH-KL01 |
|---------------------|--------------------------------------|
| Power supply | 110/ 220V/ 50-60Hz |
| Machine power | 0.9Kw |
| Hopper volume | 30L |
| Hopper size | About 320*410mm(Dia*H) |
| Measurement method | Volume filling |
| Filling weight | 1–500g (can be customized) |
| Filling speed | 10-30 bottles/min |
| Filling nozzle size | 20mm (other sizes can be customized) |
| Machine size | 2000*550*1800mm(L*W*H) |
| Machine weight | About 166kg |
| Package weight | About 205kg |
| | |



Automatic Bottle Powder **Filling Machine**

This automatic filling machine is designed for filling powder into bottles, the filling volume can be set by entering certain number or using the filling weight. The conveyor belt can be removed and use it as a semi-automatic machine, help you save working space. It is widely used in food, daily chemical industries.

- 1. Filling nozzle size can be customized according to bottle size.
- 3. Filling volume is controlled by measuring cup.it can ensure the filling accuracy of each bottles.

| Machine model | SH-F |
|--------------------------|----------------------------------|
| Voltage | 110/220/38 |
| Main motor power | 1.2 |
| Filling type | Weight Contro |
| Filling range | About 1 |
| Suitable bottle diameter | About 2 |
| Suitable bottle height | About 6 |
| Hopper size | Abou |
| Working speed | About 1–30 |
| Machine size | About 450*650*1860mm(Machine) Ab |
| Machine weight | About |
| Package size | About 1900* |
| Package weight | About |



2. It can work with automatic capping, labeling machine to realize automted production.

-FM710 380V 50-60HZ 25KW ol or Auger Filling 10-2000g 25–150mm 60–300mm out 25L 30 bottles/min About 265*265*570mm(Weighing Device ut 128kg)*2170*820mm ut 171ka

SUNHΛN

AUTOMATIC electric liquid filling machine

Desktop type automatic filling machine can save working space and improve working efficiency. It is suitable for low viscosity liquid. It is good for beverage, cosmetic industries.

Multiple filling nozzles can be customized as production need.
4L/12L diaphragm pump can be chosen according to filling volume.
Diving nozzles can be customized according to filling material.

| Machine modelSH-DTDP4Machine Voltage110/220V 50-60HZMachine Power250WMaximum flow rate4L/min 12L/min can be chosenWorking speed1500-3000 bottles/hour(depends on bottle size and liquid)Air pressure0.3-0.4MPaFlling accuracy≤+1% (Based on water)Diameter of Flling Nozzle6/8mm |
|--|
| Machine Power250WMaximum flow rate4L/min 12L/min can be chosenWorking speed1500–3000 bottles/hour(depends on bottle size and liquid)Air pressure0.3–0.4MPaFlling accuracy≤+1% (Based on water)Diameter of Flling Nozzle6/8mm |
| Maximum flow rate4L/min 12L/min can be chosenWorking speed1500–3000 bottles/hour(depends on bottle size and liquid)Air pressure0.3–0.4MPaFlling accuracy≤+1% (Based on water)Diameter of Flling Nozzle6/8mm |
| Working speed1500–3000 bottles/hour(depends on bottle size and liquid)Air pressure0.3–0.4MPaFiling accuracy≤+1% (Based on water)Diameter of Filing Nozzle6/8mm |
| Air pressure 0.3–0.4MPa Filing accuracy ≤+1% (Based on water) Diameter of Filing Nozzle 6/8mm |
| Filing accuracy ≤+1% (Based on water) Diameter of Filing Nozzle 6/8mm |
| Diameter of Filing Nozzle 6/8mm |
| |
| |
| Delay Range 0.01–999.9s |
| Count Range 1–99999 Times |
| Size of air compressor connector OD 8mm |
| Filling Volume 3–1000m(220V)3–500ml(110V) |
| Suitable bottle height <220mm(Can be customized,max height 300mm) |



Desktop Filling And Capping Machine

This monoblock machine can fill low-viscosity liquid and tighten bottle caps automatically. Designed into desktop type, it is good for saving working space. It can be widely used in pharmaceutical, chemical, beverage, cosmetic industries.

- 1. Monoblock design with filling and capping function, it saves working space.
- 2. Equipped with 316 stainless steel magnetic pump, it has high filling precision.
- 3. Customization for multiple filling heads, cap pressing head or other filling pumps is optional.

| Machine model | SH-AFC1M |
|--------------------------|---|
| Voltage | 220V-50HZ/110V-60HZ |
| Machine Power | 500W |
| Filling Pump | Magnetic Pump |
| Working Speed | 20–50bottles/min(depending on liquid and bottle size) |
| Filling Range | ≤100ml |
| Suitable Bottle Diameter | 10-40mm |
| Suitable Bottle Height | ≤120mm(Can customize for higher bottles) |
| Suitable Cap Diameter | Can be Customized |
| Size of Filling Head | OD 6mm |
| Machine Size | About 510*510*930mm |
| Machine Weight | About 55kg |
| | |



function, it saves working space. c pump, it has high filling precision. p pressing head or other filling pumps

LABELING MACHINE

Peristaltic Pump Rotary **Filling Capping Machine**

This monoblock machine can fill low-viscosity liquid and tighten bottle caps automatically. Peristaltic pump makes it more convenient to change tube when filling different liquid. It can be widely used in pharmaceutical, chemical, beverage, cosmetic industries.

- 1. Compact design with filling and capping function, it saves working space.
- 2. With peristaltic pump, liquid only flows in tube during filling, ensuring its cleanliness.
- 3. Customization for multiple filling heads, cap pressing head or other filling pumps is optional.

| Machine model | SH-AFC1P |
|--------------------------|---|
| Voltage | 220V-50HZ/110V-60HZ |
| Machine Power | 500W |
| Filling Pump | Peristaltic Pump |
| Working Speed | 20-50bottles/min(depending on liquid and bottle size) |
| Filling Range | ≤100ml |
| Suitable Bottle Diameter | 10–40mm |
| Suitable Bottle Height | ≤120mm(Can customize for higher bottles) |
| Suitable Cap Diameter | Can be Customized |
| Size of Filling Head | OD 6mm |
| Machine Size | About 510*510*970mm |
| Machine Weight | About 69kg |
| | A |



Rtary Filling Capping **Machine With Conveyor**

Made in compact design with filling and capping function, the machine can save working space. It can be widely used in pharmaceutical, cosmetic, chemical, daily chemical industries.

- 3. Designed with conveyor belt, it can work with labeling machine to achieve automated production.

| Machine model | SH-A |
|--------------------------|--------------------------|
| Voltage | 220V-50HZ |
| Machine Power | 50 |
| Filling Pump | Peristal |
| Working Speed | 20-50bottles/min(dependi |
| Filling Range | ≤1 |
| Suitable Bottle Diameter | 10-4 |
| Suitable Bottle Height | ≤120mm(Can custor |
| Suitable Cap Diameter | Can be C |
| Size of Filling Head | OD |
| Conveyor Belt Size | About 670 ³ |
| | |



1. With peristaltic pump, liquid won't pass through pump during filling, ensuring its cleanliness. 2. Customization for multiple filling heads, cap pressing head or other filling pumps is optional.

> -AFC1Z Z/110V-60HZ 00W Itic Pump ling on liquid and bottle size 00ml 40mm mize for higher bottles Customized 6mm *80mm(L*W)

J 20 \mathbf{O} \blacktriangleright J ש $\mathbf{\overline{\mathbf{D}}}$

Magnetic Pump Small Filling and Capping Machine

As a monoblock machine with filling and capping function, it can help to save working space. It can be widely used in pharmaceutical, daily chemical, chemical, cosmetic industries.

- 1. Equipped with stainless steel magnetic pump, it has high filling precision.
- 2. With conveyor belt, it can work with labeling machine to realize automated production.
- 3. Customization for multiple filling heads, cap pressing head or other filling pumps is optional.

| Machine model | SH-AFC1S |
|--------------------------|---|
| Voltage | 220V-50HZ/110V-60HZ |
| Machine Power | 1000W |
| Filling Pump | Magnetic Pump |
| Working Speed | 20-50bottles/min(depending on liquid and bottle size) |
| Filling Range | ≤100ml |
| Suitable Bottle Diameter | 10–40mm |
| Suitable Bottle Height | ≤120mm(Can customize for higher bottles) |
| Suitable Cap Diameter | Can be Customized |
| Size of Filling Head | OD 8mm |
| Conveyor Belt Size | About 640*80mm(L*W) |
| Machine Size | About 580*580*1080mm |
| Machine Weight | About 75kg |
| | |



3 in 1 Automatic **Filling Capping Machine**

This machine can be used for low-viscosity liquid like essential oil, toner, eye drops, etc. It can be customized according to production need. The machine can be widely used in pharmaceutical, cosmetic, chemical, beverage industries.

1. Designed with stainless steel magnetic pump, it has high filling precision. 2. With functions of feeding caps, filling and capping bottles, it greatly saves working space. 3. It can work with labeling machine and bottle turntable, achieving automated production.

| Machine model | SH-AFC1 |
|--------------------------|---|
| Voltage | 220V-50HZ/110V-60HZ |
| Max Power | 300W |
| Filling Pump | Magnetic Pump |
| Working Speed | 0-40 bottles/min(depending on liquid,bottle and caps) |
| Suitable Bottle Diameter | 25–50mm(Can Customize) |
| Suitable Bottle Height | 50–350mm |
| Air Pressure | 0.4-0.6MPa |
| Capping Torsion | 4–9kgf/cm |
| Conveyor Size | About 2000*100mm(L*W) |
| Machine Size | About 1015*800*1560mm |
| Machine Weight | About 341kg |
| | |



 \mathbf{J} 20 \mathbf{O} $\mathbf{\Sigma}$ J 50

Flling and Capping Machine

This machine has the function of filling paste or liquid, feeding sprayer caps and bottle cover, capping bottles automatically. It can be widely used in medicine, food, daily chemical, cosmetic industries.

- 1. With pneumatic filling head, it can fill viscous liquid fast and accurately.
- 2. This machine can be customized according to production need.
- 3. With functions of cap feeding, bottle filling and capping function, it saves working space.

| Machine model | SH-AFC2 |
|--------------------------|--|
| Voltage | 220V-50HZ/110V-60HZ |
| Machine Power | 2000W |
| Working Speed | About 30 bottles/min(depending on product size and liquid) |
| Filling Material | Liquid or paste |
| Filling Rate | Depend on filling material |
| Suitable Bottle Diameter | Can be customized |
| Suitable Cap Diameter | Can be customized |



Magnetic Pump Filling And Capping Machine

This machine is designed for filling and capping credit card sprayer bottles. It can pack 50 bottles/min at max, greatly improving efficiency. It can be used in medicine, daily chemical, chemical industries.

- 1. Equipped with stainless steel magnetic pump, it has high filling precision.
- 2. With functions of filling liquid and pressing caps, it can saves working space.
- 3. This machine can be customized according to production need.

| Machine model | SH-A |
|--------------------------|---------------------------|
| Voltage | 220V-50HZ/ |
| Machine Power | 100 |
| Filling Pump | Magneti |
| Working Speed | 10-50bottles/min(dependir |
| Max Flow Rate | 2L/ |
| Suitable Bottle Diameter | Can be Cu |
| Suitable Bottle Height | Can be Cu |
| Suitable Cap Diameter | Can be Cu |
| Size of Filling Head | OD 4 |
| Machine Size | About 930*6 |
| Machine Weight | About |



mp, it has high filling precision. caps, it can saves working space. g to production need.

AFC6

- Z/110V-60HZ
- 00W
- tic Pump
- ing on liquid and bottle size)
- /min
- Customized
- Customized
- Customized
- 4mm
- 670*1080mm
- t 104kg

FILLER & CAPPER

Automatic Cup Filling **Sealing Machine**

This machine can fill paste or liquid and seal cups automatically. The machine can be customized to suit for your products. It can be widely used in food, beverage industries.

- 1. With cup feeding, filling and sealing function, it can save working space.
- 2. Working parameters can be set or adjusted on touch screen panel easily.
- 3. Filling range and rotary plate can be customized according to production need.

| Machine model | SH-FS100 |
|-----------------------|--|
| Voltage | 220V-50HZ/110V-60HZ |
| Machine Power | 1.6kW |
| Working Speed | 12-15 cups/min(depending on cup size and material) |
| Filling Range | <100ml (Customized) |
| Suitable Cup Diameter | Can be Customized |
| Air Pressure | 0.4-0.6Mpa |
| Machine Weight | About 107kg |



Automatic Filling Sealing Machine **For Plastic Ampoule Bottle**

This machine has the function of feeding, filling, capping plastic ampoule bottles automatically. It can be widely used in cosmetic, pharmaceutical industries.

- 1. With ceramic pump, it has high filling precision, suitable for small-volume filling.
- 2. The machine can be customized according to production need.
- 3. It can realize feeding, filling and capping plastic ampoule at one machine, saving working space.

| Machine model | SH-AFC5 |
|-----------------|-------------------------------|
| Voltage | 220V-50HZ/110V |
| Machine Power | ЗКW |
| Working Speed | 50–60pcs/min(depending on pro |
| Filling Range | 1–5ml (Can customize for |
| Filling Error | About 0.05% |
| Air Pressure | 0.6Mpa |
| Air Consumption | 0.38㎡/min |
| Machine Body | 304 Stainless S |
| Machine Size | About 1300*900*10 |



- -60HZ
- oduct size and liquid)
- different size)

- 650mn

\mathbf{T} 20 \mathbf{O} $\mathbf{\Sigma}$ J ס 30

Automatic Soft Tube Filling And **Ultrasonic Sealing Machine**

This machine is suitable for filling and sealing soft tubes, like toothpaste, cream, body lotion. It can be widely used in pharmaceutical, daily chemical, cosmetic industries.

- 1. With the function of feeding, filling, sealing tubes and printing date, it can greatly save working space.
- 2. With the way of ultrasonic sealing, it can seal tubes firmly and beautifully.
- 3. The machine can be customized as needed.

| Machine model | SH-FS009U |
|----------------------|---|
| Voltage | 220V-50HZ/110V-60HZ |
| Machine Power | 2.6KW |
| Working Speed | 18-28pcs/min(depending on tube size and material) |
| Filling Range | 6-60ml/10-120ml/25-250ml |
| Filling Accuracy | ±1% |
| Hopper Capacity | 30L |
| Sealing Diameter | 16–50mm |
| Sealing Height | 70–210mm |
| Sealing Method | Ultrasonic Sealing |
| Ultrasonic Frequency | 20KHz |
| Air Pressure | 0.6Mpa |
| Application | Aluminum-plastic soft tube/Plastic soft tube |
| Machine Size | About 1615*1400*1590mm |
| | |



Automatic Soft Tube Filling **And Sealing Machine**

This machine is designed for filling and sealing single-dose strips. With the way of ultrasonic sealing, it can seal strips firmly. It can be equipped with letter fonts, helping to print date on products.

- 2. It can realize filling and sealing at one machine, greatly saving working space.
- 3. The machine can be customized according to production need.

| Machine model | SH-FS50U |
|-------------------------|---|
| Voltage | 220V-50HZ/110V-60HZ |
| Machine Power | 2.6KW |
| Filling Pump | Ceramic Pump |
| Working Speed | 10–13 rows/minute(depending on product size and liquid) |
| Filling Error | ±0.05g |
| Sealing Diameter | 50–140mm |
| Sealing Height | 50–200mm |
| Frequency | 20KHz |
| Air Pressure | 0.6Mpa |
| Ultrasonic Electric Box | 20K 2600W digital automatic frequency tracking electric box |
| Machine Body | 304 Stainless Steel |
| Machine Size | About 1300*1010*1550mm |
| Machine Weight | About 350kg |
| | |



1. Equipped with ceramic pump, it has high filling accuracy, suitable for small-volume filling.



\mathbf{J} 20 \mathbf{O} $\mathbf{\Sigma}$ ס 30

Automatic particle powder packaging machine

This machine is designed for filling and sealing powder pouch. With the way of weighing and filling, it can fill materials accurately. Filling range and sealing type of the machine can be customized as needed.

- 1. With bag filling, forming and sealing function, it can save working space.
- 2. It can be equipped with date coder, which can print date or batch on bags.
- 3. Easy operation: Set filling weight directly to realize accurate filling.

| Machine model | SH-GZ200 |
|---------------------------|---|
| Voltage | 220V-50HZ/110V-60HZ |
| Machine Power | 360W |
| Working Speed | 15–25bags/min(depending on bag size and products) |
| Filling Range | 1–50g(Can be customized) |
| Sealing Method | Three Side Sealing |
| Suitable Packing Material | Heat Sealable Bags |
| Machine Weight | 49kg |



Automatic Paste Filling **And Sealing Machine**

With the function of filling paste and sealing bags, it can greatly saves working space. The machine can be used in food, daily chemical, chemical industries.

- 1. With mixing function, it ensures the materials can be filled equably.
- 2. It can be equipped with date coder, which can print date or batch on bags.
- 3. Filling range and sealing type can be customized as needed.

| SH-G | Machine model |
|-------------------------|------------------------|
| 220V-50HZ | Voltage |
| 45 | Machine Power |
| 15–25 bags/min(dependin | Working Speed |
| 3–50ml(Can k | Filling Range |
| ±0 | Filling Error |
| Back Side(We also of | Sealing Method |
| PP/PE/I | Suitable Film Material |
| About 500*S | Machine Size |
| Abou | Machine Weight |



GFGT50 Z/110V-60HZ 50W ng on bag size and material) be customized)).5ml ffer three sides sealing POF/PVC 900*1800mm ut 63kg





\mathbf{J} 20 S \mathbf{D} $\mathbf{\overline{\mathbf{D}}}$

Automatic Back **Sealing Machine**

With functions of filling powder, sealing bags and printing date, it can help to save working space. Filling range and sealing type of the machine can be customized as needed.

- 1. With bag filling, forming and sealing function, it greatly saves working space.
- 2. Equipped with date coder, it can help to print date or batch on bags.
- 3. Easy operation: Set filling weight directly to realize accurate filling.

| Machine model | SH-GFGT50 |
|---------------------------|--|
| Voltage | 220V-50HZ/110V-60HZ |
| Machine Power | 360W |
| Working Speed | 5–25bags/min(depending on bag size and products) |
| Filling Range | 1-50g(Can be customized) |
| Sealing Method | Back Side Sealing |
| Suitable Packing Material | Heat Sealable Bags |
| Machine Weight | About 58kg |



Automatic Granule **Packaging Machine**

This machine has the function of filling powder or granules, sealing bags automatically. With the way of measuring cup filling, it can fill materials precisely and quantitatively. It can be used in food, medicine industries.

2. It can be equipped with date coder, helping to print date or batch on bags. 3. Filling range, measuring cup size and sealing type can be customized as needed.

1. With function of filling, forming and sealing bags, it can save working space.

| Machine model | SH-K100 |
|---------------------|---|
| Voltage | 220V-50HZ/110V-60HZ |
| Machine Power | 1.6KW |
| Working Speed | 35-70bags/min(depending on bag size and material) |
| Packing Capacity | 5–100ML |
| Finished Bag Length | 50–170mm |
| Finished Bag Width | 25–120mm |
| Packing Film Width | 60–240mm |
| Air Power | 0.6Mpa |
| Air Consumption | 100L/min |
| Machine Weight | 300KG |
| | |









 \mathbf{J} 20 S \mathbf{D} J

Automatic fluid and semi-fluid packagingmachine

This machine has the function of filling paste, sealing bags and printing date automatically. It can pack 30–60 bags/min, greatly improving efficiency. The machine can be used in food, daily chemical industries.

- 1. With bag filling, forming and sealing function, it greatly saves working space.
- 2. Equipped with date coder, it can help to print date or batch on bags.
- 3. Filling range and sealing type can be customized as needed.

| Machine model | SH-S100 |
|---------------------|---|
| Voltage | 220V-50HZ/110V-60HZ |
| Machine Power | 1.6kW |
| Working Speed | 30-60bags/min(depending on bag size and material) |
| Packing Capacity | 5–100ml |
| Finished Bag Length | 40–150mm |
| Finished Bag Width | 25–120mm |
| Packing Film Width | 60–240mm |
| Air Power | 0.65Mpa |
| Air Consumption | 150L/min |
| Machine Size | About 760*1380*1700mm |
| Machine Weight | About 300Kg |
| | |



Automatic Powder Packaging Machine

This machine has the function of filling powder, sealing bags and printing date automatically. It can pack 30–60 bags/min, improving working efficiency. It can be widely used in food, medicine industries.

- 1. With functions of powder filling, bag forming and sealing, it can save working space.
- 2. With date coder, it can help to print date or batch on bags.
- 3. Filling range and sealing type can be customized as needed.

| Machine model | SH-F100 |
|---------------------|--|
| Voltage | 220V-50HZ/110V-60HZ |
| Machine Power | 1.6kW |
| Working Speed | 30-60bags/min(depending on bag size and materials) |
| Packing Capacity | 5–100ml |
| Finished Bag Length | 50–170mm |
| Finished Bag Width | 25–120mm |
| Packing Film Width | 60–240mm |
| Air Power | 0.6Mpa |
| Air Consumption | 100L/min |
| Machine Size | About 760*980*1700mm |
| Machine Weight | About 310kg |
| | |



ing and sealing, it can save working space. or batch on bags. omized as needed.

FILLER & SEALER