

TECHNICAL SPECIFICATIONS

TEST	LIN 635	UOM	TEST METHOD
FABRIC PROPERTIES			
Fiber Content	50/50% - Polyester/Cotton		
Weight (±5%)	225	g/m ²	ISO 3801
TENSILE STRENGTH			
Warp / Weft	>1200 / >600	Newton	ISO 13934-1
TEAR STRENGTH			
Warp / Weft	>75/ >30	Newton	ISO 13937-2
RUBBING FASTNESS			
Dry / Wet	≥4 / ≥4	Grade	ISO 105-X12
SHRINKAGE			
Warp / Weft	≤2 / ≤1	%	ISO 7771
ANTIFUNGUS TEST			
Soil Burial	≤10	%	ISO 11721-1:2001
FIRE RETARDANT TEST			
Fire Retardant	Pass	- - -	NFPA 701

PRODUCT DESCRIPTION

LIN 635 is a non durable fire retardant that complies with NFPA 701 FR standards. This is a UNICEF / Red Cross specified fabric used for tent inner lining and outdoor applications.

APPLICATIONS

Tent Inner Lining

COLORS



Natural

- Custom colors available on request.

PACKING DETAILS

WIDTH

84 INCH | 213 CM

SELVEDGE

FRINGE

ROLL LENGTH (Approx.)

54 YARDS | 50 METERS

FEATURES



Fire Retardant



Mildew Resistant



Breathable