

Natrula® RS FR 15 oz

TECHNICAL SPECIFICATIONS

TEST	NATRULA RS FR 15 OZ	UOM	TEST METHOD
FABRIC PROPERTIES			
Fiber Content	Cotton		
Weight (±5%)	575	g/m ²	ISO 3801
TENSILE STRENGTH			
Warp / Weft	>2100 / >1800	Newton	ISO 13934-1
TEAR STRENGTH			
Warp / Weft	>70 / >55	Newton	ISO 13937-2
RUBBING FASTNESS			
Dry / Wet	≥4 / ≥4	Grade	ISO 105-X12
SHRINKAGE			
Warp / Weft	≤3 / ≤1	%	ISO 7771
RESISTANCE TO WATER			
Spray Rating	>80	%	ISO 4920
Water Column	>500	MM	ISO 811
LIGHT FASTNESS			
Light Fastness	7	Grade	ISO 105-B02:2013
ANTIFUNGUS TEST			
Soil Burial	≤10	%	ISO 11721-1:2001
FIRE RETARDANT TEST			
Fire Retardant	Pass	- - -	CPAI-84 BS 7837 & BS 3408

PRODUCT DESCRIPTION

Natrula® RS FR 15 Oz is a tightly woven plain weave canvas fabric made with high strength ring spun cotton yarns.


This performance fabric has waterproof, water repellent, anti-mildew and high light fast properties. The fabric is also breathable making it suitable for tenting applications.

It has a Durable Fire Retardant finish which complies with the CPAI-84 FR standard.

APPLICATIONS

Tents | Boat Cover | Outdoor Covers | Campers | Industrial Covers & Curtains

COLORS



Palm Green

• Custom colors available on request.

PACKING DETAILS

WIDTH

72 INCH | 183 CM

SELVEDGE

FRINGE

ROLL LENGTH

54 YARDS | 50 METERS

FEATURES



Fire Retardant



Waterproof



Water Repellent




Color Fastness



Mildew Resistant



Breathable



Dimensionally Stable



www.rhinotuffcanvas.com

V.4.23