Neplar® fr 12 oz

TECHNICAL SPECIFICATIONS

TEST	NEPLAR FR 12 OZ	UOM	TEST METHOD
FABRIC PROPERTIES			
Fiber Content Weight (±5%)	50/50% - Polyester/Cotton 500	g/m²	ISO 3801
TENSILE STRENGTH			
Warp / Weft	>2100 / >1600	Newton	ISO 13934-1
TEAR STRENGTH			
Warp / Weft	>70 />45	Newton	ISO 13937-2
RUBBING FASTNESS			
Dry / Wet	≥4 / ≥4	Grade	ISO 105-X12
SHRINKAGE			
Warp / Weft	≤2 / ≤1	%	ISO 7771
RESISTANCE TO WATER			
Spray Rating	>60	%	ISO 4920
Water Column	>500	MM	ISO 811
LIGHT FASTNESS			
Light Fastness	7+	Grade	ISO 105-B02:2013
ANTIFUNGUS TEST			
Soil Burial	≤10	%	ISO 11721-1:2001
FIRE RETARDANT TEST			
Fire Retardant	Pass		CPAI-84 BS 7837 & BS 3408

PRODUCT DESCRIPTION

Neplar® FR 12 Oz is a medium weight fire retardant, waterproof canvas fabric. It is a high performance versatile polycotton fabric.

The canvas fabric it is treated with our superior impregnation treatment that locks in the waterproofing, water repellant, anti rot and mildew properties.

The fabric also has high UV resistant properties which helps facing continuous, direct sun.

It has a durable fire retardant finish which complies with the AS1530 and equivalent standards. The FR chemistry, imported from Germany is the best in class and does not leach out in the environment.

The canvas has clean ultrasonic trimmed selvedges which are not wavy or curly. The fabric lays flat and is easy to sew.

APPLICATIONS

Glamping Tents | Safari Tents | Annexe Roofs & Walls | Camper Trailer Covers Tarpaulins | Tool Bags | Caravan Walls & Awnings | Camping Gear & Accessories

COLORS

















Sandy Brown







Light Grey









Camel



Dark Olive





• Custom colors available on request.



80 INCH | 203 CM

PACKING DETAILS

SELVEDGE

WIDTH

FRINGE & ULTRASONIC SLIT

ROLL LENGTH

44 YARDS | 40 METERS

FEATURES





Fire Retardant

Water Repellent





Waterproof

Mildew Resistant





Color Fastness



Dimensionally Stable

UV Stable