# Neplar® fr 8 oz

## **TECHNICAL SPECIFICATIONS**

TEST	NEPLAR FR 8 OZ	UOM	TEST METHOD
FABRIC PROPERTIES			
Fiber Content	65/35% - Polyester/Cotton		
Weight (±5%)	400	g/m²	ISO 3801
TENSILE STRENGTH			
Warp / Weft	>1600 / >1000	Newton	ISO 13934-1
TEAR STRENGTH			
Warp / Weft	>45 / >35	Newton	ISO 13937-2
RUBBING FASTNESS			
Dry / Wet	≥4 / ≥4	Grade	ISO 105-X12
SHRINKAGE			
Warp / Weft	≤2 / ≤1	%	ISO 7771
RESISTANCE TO WATER	1		
Spray Rating	>90	%	ISO 4920
Water Column	>550	MM	ISO 811
LIGHT FASTNESS			
Light Fastness	7+	Grade	ISO 105-B02:2013
ANTIFUNGUS TEST			
Soil Burial	≤10	%	ISO 11721-1:2001
FIRE RETARDANT TEST			
Fire Retardant	Pass		CPAI-84 BS 7837 & BS 3408

## **PRODUCT DESCRIPTION**

Neplar® FR 8 Oz is a fire retardant, waterproof canvas fabric. It is a high performance versatile polycotton fabric.

The canvas fabric it is treated with our superior impregnation treatment that locks in the waterproofing, water repellant, anti rot and mildew properties.

The fabric also has high UV resistant properties which helps facing continuous,

It has a durable fire retardant finish which complies with the AS1530 and equivalent standards. The FR chemistry, imported from Germany is the best in class and does not leach out in the environment.

The canvas has clean ultrasonic trimmed selvedges which are not wavy or curly. The fabric lays flat and is easy to sew.

## **APPLICATIONS**

Camping Tents | Pop Up Tents | Annexe Roofs & Walls | Camper Trailer Roofs Caravan Walls & Awnings | Retractable Covers | bags | Loose Covers | Swags Shades | Boat Covers | Camping Gear & Accessories

#### **COLORS**









Natura

Fire Red Sand Dark Olive

• Custom colors available on request.

## **PACKING DETAILS**

**WIDTH** 80 INCH | 203 CM **SELVEDGE** FRINGE & ULTRASONIC SLIT **ROLL LENGTH** 54 YARDS | 50 METERS

#### **FEATURES**

















Dimensionally Stable

**UV Stable** 

