Neplar® R FR 6 0Z

TECHNICAL SPECIFICATIONS

TEST	NEPLAR R FR 6 OZ	UOM	TEST METHOD
FABRIC PROPERTIES			
Fiber Content Weight (±5%)	65/35% - Polyester/Cotton 270	g/m²	ISO 3801
TENSILE STRENGTH			
Warp / Weft	>1200 / >1000	Newton	ISO 13934-1
TEAR STRENGTH			
Warp / Weft	>40 / >35	Newton	ISO 13937-2
RUBBING FASTNESS			
Dry / Wet	≥4 / ≥4	Grade	ISO 105-X12
SHRINKAGE			
Warp / Weft	≤2 / ≤1	%	ISO 7771
RESISTANCE TO WATER	<u> </u>		
Spray Rating	>80	%	ISO 4920
Water Column	>300	MM	ISO 811
LIGHT FASTNESS			
Light Fastness	7+	Grade	ISO 105-B02:2013
ANTIFUNGUS TEST			
Soil Burial	≤10	%	ISO 11721-1:2001
FIRE RETARDANT TEST			
Fire Retardant	Pass		CPAI-84, AS 1530 BS 7837 & BS 3408

PRODUCT DESCRIPTION

Neplar® R FR 6 Oz is a polyester-cotton base fabric in ripstop construction. The fabric offers a unique combination of light weight and high strength. The ripstop weave brings in additional tear and tensile strength.

The canvas fabric it is treated with our superior impregnation treatment that locks in the waterproofing, water repellant, anti rot and mildew properties.

The fabric also has high UV resistant properties which helps facing continuous, direct sun.

APPLICATIONS

Camping Tents | Tipis | Shades | Awnings

COLORS



Desert sand

• Custom colors available on request.

PACKING DETAILS

WIDTH	
82 INCH 208 CM	
SELVEDGE	
FRINGE	
ROLL LENGTH (Approx.)	
44 YARDS 40 METERS	

FEATURES





Fire Retardant Water Repellent





Waterproof Mildew Resistant





Color Fastness





Dimensionally Stable

UV Stable

