

C5305 ULTRA 4K HD ALL-IN-ONE USB VIDEO CONFERENCE WEBCAM















C5305

- All in one conference cam
- Super wide 121° of view
- Bluetooth 5.0 technology

- Ultra 4K HD resolution
- Professional auto voice tracking
- Remote control

SUPERIOR PERFORMANCE

The 3-in-1 design of 4K ultra-high-definition camera, beamforming microphone, and full-range speaker reduces wiring and makes video communication easy. The built-in HF speaker voice tracking video conference camera is designed for small and medium-sized meeting rooms. It's convenient for enterprises to carry out daily business negotiations and team collaboration in different places, creating a relaxed and smooth conversation environment for improving efficiency.



WIDELY COMPATIBLE

Compatible with most common IM and conferencing Apps software, such as Skype, Zoom, Google Hangouts, FaceTime for Mac, YouTube, Facebook, Tiktok, Twitch, Whatsapp, etc.

System support: Windows7/8/10 or above, Chrome OS, Android 5.0 or above.

It works on your Computers, Laptops, Desktops, Mac, PC, LCD Monitors, Smart TV, TV BOX and more.

UHD SMOOTH STREAMING NO LAG

True-to-life 4K (3840x2160)@P30fps ultra-high-resolution clear images, and backward compatible with various resolutions such as 1080P and 720P. The built-in intelligent analysis algorithm can auto-voice tracking and frame. Meet the needs of users for different video experiences, and provide accurate communication. In any lighting condition for high-quality recording, asynchronous presentation sharing with teams, and smooth, fluid gaming broadcasts that keep up with your every move.



APPLICATION SCENARIOUS













PRODUCT SPECIFICATION

odel	C5305
ame	HD Video Conference Camera
amera	
ideo System	Ultra HD (4K), Full HD (1080p), HD (720p)
ensor	1/2.5 inch, CMOS, Effective Pixel: 8.51M
ens	121°(DFOV), 110°(HFOV), 5x digital zoom, pan/tilt ±15°
igital Zoom	5x
linimal Illumination	0.5LUX@(F1.8, AGC ON)
hutter	1/30s ~ 1/10000s
Vhite Balance	Auto, Indoor, one push, manual specified color temperature(2500K-8000K)
acklight Compensation	Support
igital Noise Reduction	2D&3D Digital Noise Reduction
ideo S/N	≥55dB
orizontal Angle of View	110
ertical Angle of View	/
orizontal Rotation Range	±170°
ertical Rotation Range	15°
an Speed Range	2.7° ~ 35.7°/s
ilt Speed Range	2.7° ~ 31.5°/s
& V Flip	Υ
mage Freeze	V
umber of Preset	2
reset Accuracy	0.1
udio	
ull Frequency Speaker	96 dB SPL in the case of 0.5 meter
licrophone Array	Beam Forming (BF) microphone, the pickup distance is 6 meters
xtended MIC	Support(Optional)
SB Featured	
perate System	Windows7/8/10 or above, Chrome OS, Android 5.0 or above
olor System/Compression	YUV 4:2:2/H.264/MJPEG
udio on USB	32K sampling rate, support UAC1.0
IVC Protocol	UVC 1.1~1.5
VC PTZ	Support
PC Features	
ideo Commpression	H.264 / MJPEG /YUY2 /NV12
Iain Stream Resolution	3840x2160, 1920x1080, 1280x720, 640x480
nput/Output Interface	
D Output	1 * HDMI, Version 1.4b
SB Interface	1 * USB3.0, Type C ; 1 * USB2.0, Type A ;
ower Jack	DC 12V, 2A(Max)
eneric Specification	
ontrol Method	2.4G Remote Controller
nstallation Method	Desktop, Wall, TV and others
perating Temperature	0°C ~ 40°C
torage Temperature	-40°C ~ 60°C
imensions	600mm * 115mm * 135mm(holder included)
et Weight	2.5KG

