



Simple setup and stable connection

- Compatible with various devices Applicable to 60 square meters conference room with Extension

- 360° Voice Pick-Up **Noise Cancellation** Wireless adapter







connection



omnidirectional Microphone with a transmission distance of


up to 5 meters, which can achieve 360" voice pick-up, so


EX AUDIO LECI



calls sound their best on both ends. Which can bring you a good interactive experience and create the best conference call experience for you.

built-in 4 high-sensitivity microphones array, 360







RADVISION' Delivering the Visual Experience

BlueJeans

WIDE COMPATIABLITY

vidtel 🐠 webex vMix Nidyo ≀

. 1 | 1 . 1 | 1 .

GoToMeeting

Compatible with mainstream online voice calling services (PolyCom, Blue Jeans, Cisco, Vmix, GoToMeeting, Radvision,

SeeVogh, WebEx, Easy meeting, Vidtel and working with Microsoft Lync Software, and ZOOM.US, SKYPE, VIDYO etc), you can enjoy great sound quality and comfort at the same



time.

Polycom[®]













L > Lync

Build-in 4000mAh lithium Rechargeable battery, full charge in up to 4 hours, up to 10 hours use after a full charge

LONG BATTERY LIFE

| 4000mAh

Stop collecting sound

ONLINE EDUCATION

PERSONAL ENTERTAINMENT

152*152*40mm

495*405*220mm

0.46KG

PC/ABS

199*189*94mm

10

0.81KG

152*152*40mm

495*405*220mm

0.36KG

PC/ABS

199*189*94mm

10

0.69KG

A circular array of built-in four_

Specification(SpeakerPhone)

Specification(Extension Unit)

APPLICATION SCENARIOS

VIDEO CONFERENCING

TELE-MEDICAL

Product dimension

Product weight(g)

Package dimension

Packing quantity(Pcs)

Packing weight (g)

Product weight(g)

Package dimension

Packing weight (a)

Carton) Carton Dimensions

(Length×width×Height mm)

(L×W×H mm)

Material

(L×W×H mm)

Carton) Carton Dimensions

(Length×width×Height mm)

(W×H mm)

Material



Product dimension (W×H mm) Carton) Carton Dimensions (Length×width×Height mm)

L downing realigne (g)	0.0710	
Meeting capacity		
Covering area	15-30 SQM	
Covering area (+Extension Unit)	30-60 SQM	
Microphone		
Microphone type	Omnidirectional microphone	
Pickup distance	4-8 meters	
SNR	65dB	

Microphone array	omnidirectional microphones,360°pick-up	
Frequency response	100Hz~22kHz	
Reproducer		
Reproducer type	Full frequency reproducer	
Rate of power	Max output 5W, effective 3W	
Volumo	85dRA (in the range of 1m)	

Audio frequency	
Frequency range	150Hz ~ 22kHz
Sensitivity	85 dB SPL (in the range of 0.5m)
Volume	85dBA (in the range of 1m)
•	

48K Sampling rate, HD broadband audio, **Audio features** full duplex audio **USB** protocol **UAC 2.0** Echo cancellation Support

Noise suppression Support Support Gain control **Connection mode**

Wireless adapter wireless receiving distance 10 meters Power supply

USB Dongle,

An extension unit can be added through an

Maximum charging current: 2A;

0°C-40C

CCC, CE, RoHS, FCC

Windows 7, Windows 8, Windows 10, Linux,

Omnidirectional microphone, USB cable,

Duration: 10 hours;

USB A interface, the external power supply supplies power to the CM600 device through the USB B interface; **Light touch button** (mute button with light indicator) button

Connect with terminal equipment through Line in/out 3.5mm four-core audio cable USB data communication, audio input/call **USB** wired

Extension ports

Rechargeable battery

System Requirements

Package contents

Work temperature

Certification

Environment condition Battery specification: 4000mAh; Full charge time: 4 hours (5V/2A);

RJ45 extension cable

Color Black Packing type Leather box **Others**

Mac OS X, Android

Quick start guide