### FEATURES AND SPECIFICATIONS



## **Features and Benefits**

The Molex PowerCat 6A Shielded Patch Cords are key components of the PowerCat 6A Shielded end-to-end solution.

Molex PowerCat 6A Shielded Patch Cords were specifically designed to support high speed data networks for 10-Gigabit Ethernet (10GBASE-T) applications. The patch cable is made from high quality shielded four pair 26AWG stranded wire. Available in a range of colors and lengths, PowerCat 6A Shielded patch cords are preterminated with RJ45 shielded plugs and feature overmolded anti-snag strain relief boots.

Molex recommends the full range of PowerCat 6A
Shielded products be used in a end-to-end system to
maximize cabling performance. This system is compliant
with latest ISO/IEC 11801 A1.1 draft and ratified TIA/EIA
568-B.2-10 for the support of 10G BASE-T.

- Shielded 4 pair 26AWG stranded cable
- Pre-terminated with WE8W shielded plugs
- Over-moulded anti-snag strain relief boots
- Suitable for EIA 568A/B wiring applications
- C6A Performance when installed as a complete PowerCat 6A Shielded System
- PVC jacket
- RoHS Compliant

## **Commercial Standards**

TIA/EIA-568-B.2-10 ISO/IEC 11801 A1.1 FCC Subpart F 68.5 IEC-603-7

Pending Approvals: ETL independant testing UL-1863 CSA C2.2

# **Technical Information**

Cable

Conductor Size: 26AWG stranded bare copper Screen material: Aluminium/polyester shield

with tinned copper drain wire

Max OD: 6.5mm Jacket: PVC

Temperature Range: -20°C to +60°C

# **Mechanical Characteristics**

Plug

Operating Life: Minimum 750 insertion cycles


Contact Material: Copper Alloy

Contact Plating: 1.25 micrometres Au/Ni

Plug dimensions & tolerances compliant with FCC Part 68 IEC 60603-7

### **Electrical Characteristics**

Max Voltage: 150 VAC (max)
Max Current: 1.5A @ 25°C
Operating temperature: -40° to 85°C



## ORDERING INFORMATION

Order No.	Description
PCD-00700-**	PowerCat 6A Shielded Patch Cord 568A/B 1M
PCD-00701-**	PowerCat 6A Shielded Patch Cord 568A/B 2M
PCD-00702-**	PowerCat 6A Shielded Patch Cord 568A/B 3M
PCD-00703-**	PowerCat 6A Shielded Patch Cord 568A/B 5M
PCD-00704-**	PowerCat 6A Shielded Patch Cord 568A/B 7M
PCD-00705-**	PowerCat 6A Shielded Patch Cord 568A/R 10M

Insert colour code in place of \*\* in part number when ordering PowerCat 6A Accessories: OH- Blue, OE-Grey, OK-Yellow, BK-Black, OC-Red, OJ-Green

## **MOLEX PREMISE NETWORKS**

Corporate Headquarters Tel: 630 969 4550 www.molexpn.com European Headquarters Tel: 44 (0) 1489 572111 www.molexpn.co.uk Pacific Rim Headquarters Tel: 61 3 9971 7111 www.molexpn.com.au