

FIBER-OPTIC PATCH-CORDS MM OM3 DX

Datasheet



Patch-cord MM OM3 DX LCPC-LCPC

Scope of supply:

- Patch-Cord
- Test report printed on P/N Label

1 pc

TECHNICAL DATA

Duplex Cable

Criteria		Value	Standard
Cable \varnothing [mm]		2.0 (\pm 0.1)	
Material		LSZH	
Secondary coating	Diameter [μ m] Material	900 (\pm 5%) LSZH	
Nominal weight [kg/km]		3.7	
Temperature range [$^{\circ}$ C]	Storage Installation Operation	-25 up to +60 -10 up to + 50 -20 up to + 60	IEC 61300-2-22
Maximum tensile strength [mm]	Installation Operation	200 100	IEC 60794-1-2 E1
Minimum bending radius [mm]	Installation Operation	50 25	IEC 60794-1-2 E11
Compressive strength [N/10cm]	Short term Permanent	250 100	IEC 60794-1-2 E13
Heat of combustion [MJ/m]		0.08	

Fiber types available

Description	ISO/IEC 11801 EIA/TIA	IEC 60793-2-10
Multimode (as per standard ITU-T G.651)	OM1	A1a.1
	OM2	A1a.1
	OM3	A1a.2
	OM4	A1a.3
	OM5	A1a.4

Optical properties (as per IEC 61753-1)

Description		Grade B/2	Grade C/2	Grade D/3
Insertion loss IL [dB]	97%	\leq 0.35	\leq 0.50	\leq 1.00
	Typical value	\leq 0.12	\leq 0.25	\leq 0.50
Return loss RL [dB]	97%	\geq 45	\geq 45	\geq 35
	Typical value	\geq 55	\geq 55	\geq 45

FIBER-OPTIC PATCH-CORDS MM OM3 DX

Datasheet

Mechanical properties

Criteria		Value	Standard
Mating durability [times]		500x (minimum)	IEC 61300-2-2
Retention [N / s]	Cable Pigtail	100 / 120 5 / 60	IEC 61300-2-4
Vibration		10-55Hz, 1 octave / min. 3 axis of 15 cycles, 0.5h / axis amplitude 0.75 mm	IEC 61300-2-1
Repeated bending [100 Cycles]	Cable Pigtail	Load 5N (-90° / 0° / +90° / 0°C Load 0.2N (-90° / 0° / +90° / 0°C)	IEC 61300-2-44
Static side load [N / min]	Cable Pigtail	1 / 60 0.2 / 5	IEC 61300-2-42
Drop [m]		1.5 (5 times)	IEC 61300-2-12

Part Numbers P/N

P/N	Description	P/N	Description
R222181	PC-DX-LCPC-LCPC-2MM-OM3-1.0M		
R222136	PC-DX-LCPC-LCPC-2MM-OM3-2.0M		
R222111	PC-DX-LCPC-LCPC-2MM-OM3-3.0M		
R222163	PC-DX-LCPC-LCPC-2MM-OM3-5.0M		
R222123	PC-DX-LCPC-LCPC-2MM-OM3-10.0M		
R222155	PC-DX-LCPC-LCPC-2MM-OM3-15.0M		
R222154	PC-DX-LCPC-LCPC-2MM-OM3-20.0M		
R223335	PC-DX-LCPC-LCPC-2MM-OM3-120.0M		