

**Patch Cord Cat.6, U/UTP, 4P, LSZH, Red, RJ45/u - RJ45/u**

---

**DESCRIPTION**

Cable Identification : U/UTP  
Outer Jacket : LSZH  
Outer Diameter :  $5.0 \pm 0.5$  mm  
Weight :  $78.000 \pm 6.0$  G

**TECHNICAL DATA**

---

Standardisation	Compliant with Cat.6 requirements of ISO/IEC 11801, EN 50173, EN 50168 and EIA/TIA 568.C.x
Cable Class	Patch Cord
Connector Class	Connector
Connector Type	RJ45
Protection Class IP	IP20
Category	Cat.6
Cu Cable Shielding	U/UTP
Min. Bend Radius	4 x O.D.
Dielectric Withstanding Voltage	1000VAC, 1min. (60Hz)
Insulation Resistance	500 MO (min.)
Current Rating	1.5A (Max.) @ 25°C
Cable Shielding	U/UTP
Number of Conductors	8
Stranding	4 X 2P Cable
Jacket Material	LSZH
Cable Jacket Characteristics	Cable, Metal-Free
Cable Overall Diameter	$5.0 \pm 0.5$ mm
Conductor Size	24 AWG (26/7)
Conductor Type	Stranded Conductor
Color	Cable Red

**Patch Cord Cat.6, U/UTP, 4P, LSZH, Red, RJ45/u - RJ45/u**

---

<b>Description</b>	<b>Part Code</b>
Patch Cord Cat.6, U/UTP, 4P, LSZH, Red, RJ45/u - RJ45/u, 1 Mtrs	R196168
Patch Cord Cat.6, U/UTP, 4P, LSZH, Red, RJ45/u - RJ45/u, 2 Mtrs	R196111
Patch Cord Cat.6, U/UTP, 4P, LSZH, Red, RJ45/u - RJ45/u, 3 Mtrs	R196112
Patch Cord Cat.6, U/UTP, 4P, LSZH, Red, RJ45/u - RJ45/u, 5 Mtrs	R196013
Patch Cord Cat.6, U/UTP, 4P, LSZH, Red, RJ45/u - RJ45/u, 10 Mtrs	R196114
Patch Cord Cat.6, U/UTP, 4P, LSZH, Red, RJ45/u - RJ45/u, 15 Mtrs	R196115
Patch Cord Cat.6, U/UTP, 4P, LSZH, Red, RJ45/u - RJ45/u, 20 Mtrs	R196118