


090.6508

**Description**

Fitted with SC-Duplex PC connector & LC-Duplex PC Connector.

Connector color: beige.

Fiber: MM G50/125 (OM3).

Cable: F8 2.0x4.1 mm,

Weight

Technical Data

Standardisation	SC connector acc. to IEC 61754-20, ISO/IEC-11801-OM3,EIA/TIA-568.C.3
Cable class	Patch Cord
Connector class	connector
Number of connectors (A)	1
Connector type (A)	SC Duplex
Protection class (IP) connector (A)	20
Polishing connector (A)	PC
Attenuation grade IL - connector (A)	Bm
Return loss grade RL - connector (A)	3
Connector color (A)	Biege
Lever- frame-coding connector (A)	Color
Number of connectors (B)	1
Connector type (B)	LC Duplex
Protection class (IP) connector (B)	20
Polishing connector (B)	PC
Attenuation grade IL - connector (B)	Bm
Return loss grade RL - connector (B)	3
Connector color (B)	Biege
Lever- frame-coding connector (B)	Color
Cable design	I-V(ZN)H
Patch Cord type	Duplex Figure 8
Fiber class	OM3
Cable jacket material	LSZH
Cable jacket characteristics	cable, metal-free
Cable jacket characteristics	zero-halogen
Cable overall diameter	F8 2.0x4.1 mm (± 0.15)
Conductor type	tight buffer
Fiber / conductor diameter	G50/125 μ m
Fiber type	Multimode (MM)
Length (meter)	3