

# Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 14.04.2010

Revision: 14.04.2010

## 1 Identification of the substance/preparation and of the company/undertaking

- **Product details**

- **Trade name:** FUCHS SILKOPEN

- **Article number:** 800002686

- **Application of the substance / the preparation** Penetrating oil

- **Manufacturer/Supplier:**

FUCHS LUBRICANTS (UK) PLC.

New Century Street

Hanley

Stoke-on-Trent, Staffordshire, ST1 5HU

UK

Emergency telephone: (UK) 08701 200400

e-mail: product.safety@fuchs-oil.com

- **Further information obtainable from:** Product safety department.

- **Information in case of emergency:** Emergency telephone: (UK) 08701 200400

## 2 Hazards identification

- **Hazard description:**



F+ Extremely flammable

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Warning! Pressurized container.

R 12 Extremely flammable.

R 66 Repeated exposure may cause skin dryness or cracking.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

Keep out of the reach of children

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

## 3 Composition/information on ingredients

- **Chemical characterization**

- **Description:** Mixture of various multifunctional components with propellant in aerosol can.

- **Dangerous components:**

CAS: 64742-48-9 EINECS: 265-150-3	Hydrocarbon solvent, dearomatised	Xn; R 65-66	30-60%
CAS: 106-97-8 EINECS: 203-448-7	Butane	F+; R 12	5-10%
CAS: 75-28-5 EINECS: 200-857-2	Isobutane	F+; R 12	1-5%

- **Additional information:**

For the wording of the listed risk phrases refer to section 16.

Benzene content of the hydrocarbon solvent = <0.1%

GB

(Contd. on page 2)

# Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 14.04.2010

Revision: 14.04.2010

Trade name: FUCHS SILKOPEN

(Contd. of page 1)

## 4 First aid measures

- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**  
Immediately wash with water and soap and rinse thoroughly.  
If skin irritation continues, consult a doctor.
- **After eye contact:**  
Check for and remove any contact lenses.  
Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**  
Wash mouth out with water  
Do not induce vomiting; call for medical help immediately.
- **Information for doctor:** Contains petroleum distillates

## 5 Fire-fighting measures

- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Protective equipment:**  
Wear self-contained respiratory protective device.  
Wear fully protective suit.
- **Additional information** Cool endangered receptacles with water spray.

## 6 Accidental release measures

- **Person-related safety precautions:**  
Ensure adequate ventilation  
Keep ignition sources away - no smoking.  
Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:**  
Do not allow to penetrate the ground/soil.  
Do not allow product to reach sewage system or any water course.
- **Measures for cleaning/collecting:**  
Absorb liquid components with liquid-binding material.  
Send for recovery or disposal in suitable receptacles.  
Ensure adequate ventilation.

## 7 Handling and storage

- **Handling:**
- **Information for safe handling:**  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.
- **Information about fire - and explosion protection:**  
Do not spray onto a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Observe official regulations on storing packagings with pressurized containers.

(Contd. on page 3)

# Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 14.04.2010

Revision: 14.04.2010

Trade name: FUCHS SILKOPEN

(Contd. of page 2)

- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
  - Keep container tightly sealed.
  - Store in cool, dry conditions in well sealed receptacles.
  - Protect from heat and direct sunlight.

## 8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

### 106-97-8 Butane

WEL	Short-term value: 1810 mg/m <sup>3</sup> , 750 ppm Long-term value: 1450 mg/m <sup>3</sup> , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
-----	---

- **Additional information:** The lists valid during the making were used as basis.
- **Personal protective equipment:**
  - Select PPE appropriate for the operations taking place taking into account the product properties.
- **General protective and hygienic measures:**
  - Do not eat, drink, smoke or sniff while working.
  - Wash hands before breaks and at the end of work.
  - Do not inhale gases / fumes / aerosols.
  - Avoid contact with the eyes and skin.
- **Respiratory protection:** Use suitable respiratory protective device in case of insufficient ventilation.
- **Protection of hands:**
  - The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
  - Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**
  - The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
  - The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Protective work clothing

## 9 Physical and chemical properties

- **General Information**

<b>Form:</b>	Aerosol
<b>Colour:</b>	Grey
<b>Odour:</b>	Solvent like

- **Change in condition**
  - Melting point/Melting range:** Undetermined.
  - Boiling point/Boiling range:** Not applicable, as aerosol.

- **Flash point:** <-40°C

(Contd. on page 4)

# Safety Data Sheet

## according to 1907/2006/EC, Article 31

Printing date 14.04.2010

Revision: 14.04.2010

**Trade name: FUCHS SILKOPEN**

(Contd. of page 3)

· <b>Ignition temperature:</b>	>200°C
· <b>Self-igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <b>Explosion limits:</b>	
<b>Lower:</b>	1.8 Vol %
<b>Upper:</b>	9.5 Vol %
· <b>Density:</b>	Not determined.
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.

### 10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used and stored according to specifications.
- **Materials to be avoided:** Strong oxidising agents.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous decomposition products:** Carbon monoxide and carbon dioxide

### 11 Toxicological information

- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:**  
No irritant effect.  
Frequent or prolonged contact may irritate and cause dermatitis.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.

### 12 Ecological information

- **Information about elimination (persistence and degradability):** Inherently biodegradable
- **Behaviour in environmental systems:**
- **Mobility and bioaccumulation potential:** Product is not expected to bioaccumulate.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

### 13 Disposal considerations

- **Product:**
- **Recommendation**  
Contact waste processors for recycling information.  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.  
Used, degraded or contaminated product may be classified as hazardous waste. Anyone classifying hazardous waste and determining its fate must be qualified in accordance with state and international legislation.

(Contd. on page 5)

# Safety Data Sheet

## according to 1907/2006/EC, Article 31

Printing date 14.04.2010

Revision: 14.04.2010

**Trade name: FUCHS SILKOPEN**

(Contd. of page 4)

- **European waste catalogue**  
Waste key numbers in accordance with the European Waste catalogue (EWC) are origin-referred defined. Since this product is used in several industries, no waste key can be provided by the supplier. The waste key number should be determined in arrangement with your waste disposal partner or the responsible authority.
- **Uncleaned packaging:**
- **Recommendation:** Container remains hazardous when empty. Continue to observe all precautions.

### 14 Transport information

#### · Land transport ADR/RID (cross-border)



- **ADR/RID class:** 2 5F Gases.
- **Danger code (Kemler):** -
- **UN-Number:** 1950
- **Packaging group:** -
- **Hazard label:** 2.1
- **Description of goods:** 1950 AEROSOLS
- **Tunnel restriction code** D
- **Remarks:** Tunnel restriction code: (D)

#### · Maritime transport IMDG:



- **IMDG Class:** 2.1
- **UN Number:** 1950
- **Label** 2.1
- **Packaging group:** -
- **EMS Number:** F-D,S-U
- **Marine pollutant:** No
- **Proper shipping name:** AEROSOLS

#### · Air transport ICAO-TI and IATA-DGR:



- **ICAO/IATA Class:** 2.1
- **UN/ID Number:** 1950
- **Label** 2.1
- **Packaging group:** -
- **Proper shipping name:** AEROSOLS, flammable

### 15 Regulatory information

- **Labelling according to EU guidelines:**  
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
- **Code letter and hazard designation of product:**  
F+ Extremely flammable

(Contd. on page 6)

# Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 14.04.2010

Revision: 14.04.2010

**Trade name: FUCHS SILKOPEN**

(Contd. of page 5)

**· Risk phrases:**

- 12 Extremely flammable.
- 66 Repeated exposure may cause skin dryness or cracking.

**· Safety phrases:**

- 2 Keep out of the reach of children.
- 16 Keep away from sources of ignition - No smoking.
- 23 Do not breathe vapour/spray
- 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
- 51 Use only in well-ventilated areas.

**· Special labelling of certain preparations:**

- Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
- Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.
- Keep out of the reach of children

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**· Relevant R-phrases**

- The risk phrases shown below are for those component substances which are listed in section 3 and not for the actual finished formulation.
- Hazards are concentration dependent. Therefore for the actual hazard classification and risk/safety phrases appropriate for the actual finished formulated product refer to section 15.
- 12 Extremely flammable.
- 65 Harmful: may cause lung damage if swallowed.
- 66 Repeated exposure may cause skin dryness or cracking.

**· Department issuing MSDS:** Product safety department.**· Contact:** GORDON SHARP

-GB-