Printing date 18.10.2010 Revision: 18.10.2010

#### 1 Identification of the substance/mixture and of the company/undertaking

· Product details

· Trade name: RENOLIT EXTREME LOAD 2

· Article number: 600064969

· Application of the substance / the preparation LUBRICATING GREASE

· Manufacturer/Supplier:

FUCHS LUBRICANTS (UK) PLC.

New Century Street

Hanley

Stoke-on-Trent, Staffordshire, ST1 5HU

UK

Emergency telephone: (UK) 08701 200400 e-mail: product.safety@fuchs-oil.com

- · Further information obtainable from: Product safety department.
- · Information in case of emergency: Emergency telephone: (UK) 08701 200400

### 2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Directive 67/548/EEC or Directive 1999/45/EC Not applicable.
- · Information concerning particular hazards for human and environment:

The product does not have to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · Label elements
- · Labelling according to EU guidelines:

Observe the general safety regulations when handling chemicals.

The product is not subject to identification regulations under EU Directives and the Ordinance on Hazardous Materials (German GefStoffV).

### 3 Composition/information on ingredients

- · Chemical characterization
- · Description: A blend of highly refined mineral oils and multifunctional additives with thickener system.
- · Dangerous components:

Zinc alkyl dithiophosphate

Xi R41; № N R51/53 ≤ 2.5%

· Additional information: For the wording of the listed risk phrases refer to section 16.

#### 4 First aid measures

- · General information: No special measures required.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eve contact:

Check for and remove any contact lenses.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Wash mouth out with water

Do not induce vomiting; call for medical help immediately.

(Contd. on page 2)

Printing date 18.10.2010 Revision: 18.10.2010

**Trade name: RENOLIT EXTREME LOAD 2** 

· Information for doctor:

(Contd. of page 1)

High pressure injection injuries through the skin require prompt surgical intervention and possibly steroid therapy, to minimise tissue damage and loss of function. Because entry wounds are small and do not reflect the seriousness of the underlying damage, surgical exploration to determine the extent of involvement may be necessary. Local anaesthetics or hot soaks should be avoided because they can contribute to swelling, vasospasm and ischaemia. Prompt surgical decompression, debridement and evacuation of foreign material should be performed under general anaesthetics, and wide exploration is essential.

## **5 Firefighting measures**

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

#### **6 Accidental release measures**

- · Person-related safety precautions: Particular danger of slipping on leaked/spilled product.
- · Measures for environmental protection:

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

· Measures for cleaning/collecting:

Pick up mechanically.

Send for recovery or disposal in suitable receptacles.

· Additional information: No dangerous substances are released.

### 7 Handling and storage

- · Handling:
- · Information for safe handling: Prevent formation of aerosols.
- · Information about fire and explosion protection: No special measures required.
- · Storage:
- · Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground.
- · Information about storage in one common storage facility: Store away from oxidizing agents.
- Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.

#### 8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:

Select PPE appropriate for the operations taking place taking into account the product properties.

· General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not carry product impregnated cleaning cloths in trouser pockets.

Avoid close or long term contact with the skin.

Do not eat, drink, smoke or sniff while working.

Avoid contact with the eyes.

(Contd. on page 3)

Printing date 18.10.2010 Revision: 18.10.2010

**Trade name: RENOLIT EXTREME LOAD 2** 

(Contd. of page 2)

- · Respiratory protection: Not required.
- · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Safety glasses

· Body protection: Oil resistant protective clothing

#### 9 Physical and chemical properties

· General Information

· Appearance:

Form: Pasty Colour: Grey

· Odour: Mineral-oil-like

· Change in condition

Melting point/Melting range: Undetermined. Boiling point/Boiling range: Undetermined.

· Flash point: > 100°C · Ignition temperature: >250°C

• **Self-igniting:** Product is not selfigniting.

• **Danger of explosion:** Product does not present an explosion hazard.

· **Density:** Not determined.

· Solubility in / Miscibility with

water: Insoluble.

· Viscosity:

Kinematic at 40°C: 152 cSt

#### 10 Stability and reactivity

· Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- · Materials to be avoided: Strong oxidising agents.
- · Dangerous reactions No dangerous reactions known.
- · Dangerous decomposition products: Carbon monoxide and carbon dioxide

#### 11 Toxicological information

- · Acute toxicity:
- Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.

(Contd. on page 4)

Printing date 18.10.2010 Revision: 18.10.2010

**Trade name: RENOLIT EXTREME LOAD 2** 

(Contd. of page 3)

#### · Additional toxicological information:

The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version.

When used and handled according to specifications, the product does not have any harmful effects to our experience and the information provided to us.

### 12 Ecological information

- · Information about elimination (persistence and degradability): Inherently biodegradable
- · Behaviour in environmental systems:
- · Mobility and bioaccumulation potential: Product is not expected to bioaccumulate.
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

## 13 Disposal considerations

- · Product:
- · Recommendation

Contact waste processors for recycling information.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Delivery of waste oil to officially authorized collectors only.

Used, degraded or contaminated product may be classified as hazardous waste. Anyone classifying hazardous waste and determining its fate must be qualified in accordance with state and international legislation.

· European waste catalogue

13.02.05 (if product has been used exclusively as a mineral based non-chlorinated engine or gear lubricating oil, or as a mineral based non-chlorinated lubricating grease)

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

### **14 Transport information**

- · Land transport ADR/RID (cross-border)
- · ADR/RID class:
- · Maritime transport IMDG:
- · IMDG Class:
- · Marine pollutant: No
- · Air transport ICAO-TI and IATA-DGR:
- · ICAO/IATA Class: -
- · Transport/Additional information: Not dangerous according to the above specifications.

## 15 Regulatory information

· Chemical safety assessment A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 5)

Printing date 18.10.2010 Revision: 18.10.2010

**Trade name: RENOLIT EXTREME LOAD 2** 

(Contd. of page 4)

#### · Relevant phrases

- The risk phrases shown below are for those component substances which are listed in section 3 and not for the actual finished formulation.
- Hazards are concentration dependent. Therefore for the actual hazard classification and risk/safety phrases appropriate for the actual finished formulated product refer to section 15.

R41 Risk of serious damage to eyes.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

- · Department issuing MSDS: Product safety department.
- · Contact: GORDON SHARP

CD