



## TITAN GT1 PRO C-2 5W-30

**Premium motor oil for modern passenger cars and light commercial vehicles with or without extended service intervals. Specially developed for PSA vehicles with exhaust after treatment and turbocharger. Optimum cold starting, lower oil consumption and minimised exhaust emissions.**

### Description

TITAN GT1 PRO C-2 5W-30 is an innovative engine oil for modern cars. TITAN GT1 PRO C-2 5W-30 offers benefits to all advanced, fuel-efficient engines regardless of their emission category. TITAN GT1 PRO C-2 5W-30 keeps turbochargers clean for maintaining long-term optimum charging pressure.

TITAN GT1 PRO C-2 5W-30 provides perfect protection for exhaust gas after treatment devices such as particulate filters, CRT's or oxidation catalysts. Tests prove that TITAN GT1 PRO C-2 5W-30 reduces fuel consumption significantly compared to conventional motor oils.

### Application

TITAN GT1 PRO C-2 5W-30 fulfils all the requirements of engine oils for vehicles fitted with exhaust treatment systems. Also the product can be applied in many vehicles of Asian manufacturers if the use of a C2 engine oil is specified.

TITAN GT1 PRO C-2 5W-30 may only be used in diesel engines when in conjunction with low sulphur diesel fuel. TITAN GT1 PRO C-2 5W-30 is miscible and compatible with conventional branded engine oils. However, intermixtures with other engine oils should be avoided in order to fully utilise the product's benefits. Respectively a complete oil change is recommended when converting to TITAN GT1 PRO C-2 5W-30.

### Advantages/Benefits

- Very low levels of sulphated ash, phosphorous and sulphur protect and extend the service time of all exhaust treatment systems
- Excellent protection against wear in advanced, highly-stressed diesel and gasoline engines
- Universal use in gasoline and diesel engines which are designed to be operated with this type of fuel economy engine oil
- Reduces pollutant emissions
- Reduces the formation of deposits in engines and turbochargers.
- Low evaporation losses lower oil consumption
- Reduced fuel consumption of more than 2.5 % compared to conventional oils

### Specifications

- ACEA C2
- API SN/SM/CF

### Approvals

- PSA B 71 2290
- RENAULT RN0700

### FUCHS Recommendations

- ACEA A5/B5
- FIAT 9.55535-S1
- HONDA
- SUBARU
- SUZUKI
- TOYOTA

February 2012 GDUK Page 1 of 2

Health, Safety and Environment - information is provided for products in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products.

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products



## CHARACTERISTICS: TITAN GT1 PRO C-2 5W-30

---

Density at 15°C	DIN 51757	0.860 g/ml
Colour	DIN ISO 2049	2.5 ASTM
Flash Point, CoC	DIN ISO 2592	250°C
Dynamic Viscosity at - 30°C	DIN 51398	4900 mPas
Kinematic Viscosity at 40°C	DIN 51562-1	57 mm <sup>2</sup> /s
Kinematic Viscosity at 100°C	DIN 51562-1	10.0 mm <sup>2</sup> /s

February 2012 GDUK Page 2 of 2

Health, Safety and Environment - information is provided for products in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products.

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products