

GT5000

“Presenting” the GT5000 Series TTW ATM

Genmega introduces the GT5000 series ATM. A high performance yet economical Through-The-Wall ATM solution with the look and feel of a full bank ATM. Designed for wall or Kiosk installation, the GT5000 series makes new TTW installation or replacements a snap. Built with the same compact modular components as your existing Genmega machines and engineered for easy installation and reliable operation. The GT5000 includes high-end features like a 15" High Bright LCD which support custom advertisements and a 3-cassette cash dispenser with motorized cash presenter. A new Touch-Screen rear-service panel allows convenient and safe access for ATM Operators and Service personal.

The GT5000 series ATM is ADA compliant and Chip Card (EMV) ready, including a PCI / Interac certified encrypting PIN pad (EPP), a voice guidance system, and lighted action indicators (including lighted keypad). Features of a high end Through-The-Wall ATM with the low maintenance and reliability that Genmega delivers makes this an excellent TTW solution.



 **NationalLink**
COMPLETE ATM SOLUTIONS

(800) 363-9835 | sales@nationallink.com
www.nationallink.com

GENMEGA

GT5000

Integrated Illuminated Topper Sign

High Visibility LED Sign
Attract Customers

LCD Screen

15 inch color TFT-LCD Panel
High bright LED backlight (800cd/m²)
1024 x 768 (XGA) Resolution

Printer

80mm/3" Receipt Printer
200DPI monographic printing

PIN Entry Device

16-key alphanumeric keypad
PCI 3.0 / Interac Certified
Triple-DES (TDES) compliant EPP

Rear Service Panel

7 inch color touch screen
Backlit TFT LCD panel
800 x 480 Resolution

Communication

56Kb Internal Modem
TCP/IP Ethernet - SSL



CPU

Cortex-A8 CPU (800MHz)
DDR2 256MB SRAM memory
512MB Flash Memory
Windows CE 6.0

ADA

Voice Guidance
Lighted Transaction Guidance
Accessible Keypad Layout

Card Reader

DIP Style Magnetic Card Reader
EMV - Optional

Security

UL291 Business Hours Vault
Electronic Lock or Cencon (optional)

Cash Dispenser

Up to 3 x 1700 Note Removable Cassette
Up to 3 x 2000 Note Removable Cassette
Presenter module

Dimensions

Height = 56.7"
Width = 24.1"
Depth = 33.9"
Weight = 570 lbs

Operating Environment

Temperature range : 40°F - 95°F
Relative humidity : Non-condensing=15%-85%

Power Requirements

110/220 VAC ± 10%, 50/60 Hz, 145 Watts



www.genmega.com

GENMEGA
www.genmega.com

NationalLink
COMPLETE ATM SOLUTIONS

(800) 363-9835 | sales@nationallink.com
www.nationallink.com