METER SOFTENER

MODEL NO. 140-29-600-S-4M

CAPACITY:

MIN. 480,000 grs. @ 10 lbs./cu.ft. MAX. 600,000 grs. @ 15 lbs./cu.ft.

FLOW RATE:

100 gpm. NORMAL

140 gpm. PEAK

BACKWASH 35 gpm.

TANK SIZE: $36'' \times 72''$

COMPOSITE

MEDIA:

RESIN 20 cu.ft.

GRAVEL 500 1bs.

PIPE SIZE:

INLET 2"

OUTLET 2"

DRAIN 1"

BRINE 1/2"

METER 2"

NOTE:

ALL DASHED PIPE, VALVES.

AND FITTINGS NOT PROVIDED

SPACE REQUIRED (APPROX)

BY US WATER SYSTEMS

POLYETHYLENE CAPACITY:

BRINE TANK

500 gals.

TANK SIZE: 50" x 60"

4500 lbs./salt

BRINE VALVE: 454HF

BRINE WELL: 5"

PEAK FLOWS ARE NOT

98"L × 50"W × 95"H

WEIGHT (APPROX)


TOTAL SHIPPING 1,125 lbs. TOTAL OPERATING 2,600 lbs.

RECOMMENDED FOR EXTENDED

PERIODS OF TIME.

DO NOT SCALE DRAWING

THIS DRAWING IS ISSUED IN CONFIDENCE AND CANNOT BE REPRODUCED OR USED TO MANUFACTURE ANYTHING SHOWN OR REFERRED TO WITHOUT DIRECT WRITTEN PERMISSION FROM



 $50'' \times 60''$ BRINE TANK

SOFTENER



US WATER SYSTEMS

1209 COUNTRY CLUB RD INDIANAPOLIS, IN 46234 1-800-608-8792

GENERAL ARRANGEMENT DWG. SOFTENER GOOK

SYSTEM 4- METER

DRAWN BY:	M. CURTIS	DWG. NO.
DATE:		140-29-600-S-4M
CHECKED BY:		
PAGE 1 OF 1		