

SOFTENER

MODEL NO. 140-39-1200-DX-7

CAPACITY:

MIN. 960,000 grs. @ 10 lbs./cu.ft. (each tank)

MAX. 1,200,000 grs. @ 15 lbs./cu.ft. (each tank)

FLOW RATE:

NORMAL 205 gpm. (each tank)

PEAK 280 gpm. (each tank)

BACKWASH 65 gpm. (each tank)

TANK SIZE: 48" x 72"

COMPOSITE

MEDIA:

RESIN 40 cu.ft. (each tank)

GRAVEL 900 lbs. (each tank)

PIPE SIZE:


INLET 3"

OUTLET 3"

DRAIN 2"

BRINE 1"

METER 3"



NOTE:
ALL DASHED PIPE, VALVES,
AND FITTINGS NOT PROVIDED
BY US WATER SYSTEMS

BRINE TANK

TANK SIZE: 50" x 60"

POLYETHYLENE

CAPACITY:

500 gals.

4,500 lbs./salt

BRINE VALVE: 494

BRINE WELL: 5"

WEIGHT (APPROX)


TOTAL SHIPPING 8,480 lbs.

SPACE REQUIRED (APPROX)
154"L x 50"W x 106"H

PEAK FLOWS ARE NOT
RECOMMENDED FOR EXTENDED
PERIODS OF TIME.

DO NOT SCALE DRAWING

THIS DRAWING IS ISSUED IN CONFIDENCE AND
CANNOT BE REPRODUCED OR USED TO
MANUFACTURE ANYTHING SHOWN OR REFERRED
TO WITHOUT DIRECT WRITTEN PERMISSION FROM
US WATER SYSTEMS

		US WATER SYSTEMS <small>1209 COUNTRY CLUB RD INDIANAPOLIS, IN 46234 1-800-608-8792</small>	
		GENERAL ARRANGEMENT DWG. SOFTENER 1200K SYSTEM 7-ALTERNATING	
DRAWN BY:	M. CURTIS	DWG. NO. 140-39-1200-DX-7	
DATE:			
CHECKED BY:			
PAGE 1 OF 1			