



US Water Systems 2" Flow Single Tank Water Softener With Electronic Meter

Up to 140 GPM

5 Year Warranty On Valve & Electronics

10 Year Warranty On Tanks

1 Year On All Parts

FEATURES AND BENEFITS

User friendly Fleck 2900S control valve

shary Frech 23000 control valve

Full 2" valve for high flow rates

Premium high capacity 8% cross-linked resin

3200 NXT2 electronic controller

Up to 600,000 grain maximum capacity

NSF certified tanks which require no maintenance

Safety brine valve with air check

100% fiberglass tank construction

Resin can be upgraded to 10%

ASME tanks available upon request

Model Number	Grain Capacity	Resin Tank Size	Continuous Flow	Peak Flow	Brine Tank Size
140-29-S-120-4M	120,000 Grains	16" x 65"	40 GPM	57 GPM	24" x 50"
140-29-S-150-4M	150,000 Grains	18" x 65"	50 GPM	62 GPM	24" x 50"
140-29-S-210-4M	210,000 Grains	21" x 62"	55 GPM	77 GPM	24" x 50"
140-29-S-300-4M	300,000 Grains	24" x 72"	60 GPM	95 GPM	30" x 48"
140-29-S-450-4M	450,000 Grains	30" x 72"	75 GPM	140 GPM	39" x 48"
140-29-S-600-4M	600,000 Grains	36" x 72"	100 GPM	140 GPM	50" x 60"