

# 2815 COMMERCIAL VALVE

## 1-1/2 INCH STAINLESS STEEL CONTROL VALVE



### FEATURES • BENEFITS

- ◆ 316 grade stainless steel valve body for superior strength and durability
- ◆ Continuous service flow rate of 70 GPM with a backwash of 70 GPM
- ◆ Backwash capability commodes softener tanks up to 36" in diameter and filter tanks up to 30" in diameter
- ◆ Fully adjustable 3- or 5-cycle control for efficient and reliable water treatment system operation
- ◆ Designed for single or multiple tank systems
- ◆ Corrosion resistant, UV stabilized NEMA 3R rated cover provides protection against water intrusion
- ◆ Time-tested, hydraulically-balanced piston for service and regeneration
- ◆ One-piece seal and spacer cartridge simplifies service



TESTED and CERTIFIED by the WQA to NSF/ANSI Standard 61 Section 8 Material Safety Only.



TESTED and CERTIFIED by the WQA to NSF/ANSI Standard 372 for Lead Free Compliance.



UL recognized to 979

### CONFIGURATIONS • OPTIONS

- ◆ NPT Stainless Steel 100-240 VAC operating range with multiple power plug choices (some models)
- ◆ No hard water bypass piston
- ◆ Brine cam auxiliary switch
- ◆ Electromechanical timer auxiliary switch
- ◆ Black cover with black bezel
- ◆ Optional blue or silver bezels sold separately
- ◆ **XTR2** - Premium controller with large color LCD touch screen display offers intuitive navigation and a full complement of advanced features for system type 4 softeners and filters
- ◆ **SXT** - Large LCD display and user-selectable time clock or metered functionality for softener and filter systems
- ◆ **Electromechanical Timer**- Simple to adjust and easy to service with quick access to all internal component
- ◆ **3200 Electromechanical Timer**- 7-day or 12-day time clock operation
- ◆ **3210 Electromechanical Timer**- Meter delayed operation

## VALVE SPECIFICATIONS

Valve Material	Stainless Steel - 316 Grade
Inlet/Outlet Cycles	1-1/2" NPT 3 or 5

## FLOW RATES (50 PSI INLET) – VALVE ALONE

Continuous	70 GPM (265.0 LPM) 15 psi (1.0 bar) drop
Peak	90 GPM (340.7 LPM) 25 psi (1.7 bar) drop
Cv	18 GPM (68.1 LPM) flow at 1 psi (0.07 bar) drop
Max. Backwash	70 GPM (265.0 LPM) 25 psi (1.7 bar) drop

## REGENERATION

Downflow/Upflow	Downflow only
Adjustable Cycles	Yes
Timer Available	
XTR2:	0 - 240 min/cycle
SXT:	0 - 99 min/cycle
Electromechanical:	0 - 164 min/regeneration

## METER INFORMATION

Meter Accuracy	
1" Paddle:	0.7 - 40 GPM ± 5% (2.6 - 151.4 LPM)
1-1/2" Paddle:	1.5 - 75 GPM ± 5% (5.7 - 283.9 LPM)
Meter Capacity Range	
XTR2:	1 - 9,999,999 gal (0-99,999 m <sup>3</sup> )
SXT:	1 - 999,900 gal (0 - 3,785 m <sup>3</sup> )
1" EM Standard:	310 - 5,270 gal (1.2 - 20 m <sup>3</sup> )
1" EM Extended:	1,550 - 26,350 gal (6 - 100 m <sup>3</sup> )

1-1/2" EM Standard:	625 - 10,625 gal (2.5 - 40 m <sup>3</sup> )
1-1/2" EM Extended:	3,125 - 53,125 gal (12 - 200 m <sup>3</sup> )

EM = Electromechanical

## DIMENSIONS

Distributor Pilot / Riser Tube Diameter	1.9" OD Tube (48.3 mm)
Drain Connection	1-1/2" NPT
Brine Valve	1/2" OD Tube (13 mm)
Injector System	1720
Mounting Base	4" - 8 UN
Height from Top of Tank	9" (229 mm)
Riser Height	0.25" (6.3 mm) below flush ± 0.25" (6.3 mm)

## TYPICAL APPLICATIONS

Water Softener	14 - 36" (356-914 mm) diameter
Filters	14 - 30" (356-762 mm) diameter based on 10 GPM/ft <sup>2</sup>

## ADDITIONAL INFORMATION

Electrical Rating	24/100-240V 50/60 Hz 40VA max.
Estimated Shipping Weight	22 lbs. (10 kg.)
Pressure	
Hydrostatic:	300 psi (20 bar)
Working:	20 - 125 psi (1.4 - 8.5 bar)
Water Temperature	34 - 150°F (1 - 66°C)



13845 Bishops Dr. | Suite 200 | Brookfield, WI 53005 | United States  
P: 262.238.4400 | Customer Care: 630.307.3000 | tech-support@pentair.com

§For a detailed list of where Pentair trademarks are registered, please visit [waterpurification.pentair.com/brands](http://waterpurification.pentair.com/brands). Pentair trademarks and logos are owned by Pentair plc or its affiliates. Third party registered and unregistered trademarks and logos are the property of their respective owners.

Pentair is an equal opportunity employer.

© 2018 Pentair Residential Filtration, LLC. All rights reserved.

4004630 Rev A JL18