

MEECO MANUFACTURING

9100 15TH PL S
SUITE – E
SEATTLE, WA 98108
P: 206-262-8340
F: 206-262-8343



INSTALLATION INSTRUCTIONS FOR THE THRUWALL™ ROOM TO ROOM FAN



READ AND SAVE THESE INSTRUCTIONS IMPORTANT NOTICE

WARNING - To Reduce The Risk Of Fire Or Electric Shock, Do Not Use This Fan With A Solid-State Speed Control Device. With the use of any electrical appliance, it is important to observe all basic precautions to minimize the risk associated with use, such as electrical shock, fire, or injury to persons.

If you have doubts or are unfamiliar with this type of installation work, seek the services of a qualified electrician. Suncourt assumes no responsibility for installation of the ThruWall™ Fan. Suncourt does not provide electrical connection information. For your safety and protection follow all instructions and adhere to applicable building and/or electrical codes.

Not for bathroom use.

Do not use in wet or damp locations.

Do not use in a window.

Do not install in fire rated walls.

This fan is not to be installed in an outside wall.

Use only a grounded wall outlet.

Do not operate any fan with a damaged cord or plug. Discard fan or return to an authorized service facility for examination and/or repair.

Do not run cord under carpeting. Do not cover cord with throw rugs, runners, or similar coverings. Do not route cord under furniture or appliances. Arrange cord away from traffic area and where it will not be tripped over.

NEVER EXPOSE YOUR THRUWALL™ TO TEMPERATURES OVER 140°F (60°C)

WARNING - To Reduce The Risk Of Fire, Electric Shock Or Injury To Persons,

Observe The Following:

1. Installation work and electrical wiring must be done by qualified person(s) in accordance with all applicable codes and standards, including fire-rated construction.
2. When cutting or drilling into wall or ceiling, do not damage electrical wiring or other hidden utilities.
3. Do not use any type of speed control.

Thank you for buying this Suncourt product.

The ThruWall™ fan moves air from room to room quietly and efficiently. Simple to install in any frame wall from 3-3/4" to 6-1/2" thick. A high quality Thermally Protected motor with balanced fan blade moves up to 110 CFM. Move heated or cooled air between rooms.

PLEASE READ THESE INSTRUCTIONS BEFORE STARTING INSTALLATION

The ThruWall™ can be mounted in any normal drywall or paneled stud construction wall with a 3-3/4" to 6-1/2" total thickness.

Start by making sure that there are NO studs, water, drain, electrical or other obstruction in the wall where you wish to install the unit. The power cord of the ThruWall™ is 10 ft long, please verify that the power cord will reach a 110 Volt AC outlet. The use of extension cords is not recommended. Please see the airflow direction label on the housing.

The grilles of your ThruWall™ fan may be painted to suit any decor. Thoroughly wash the grilles with mild household detergent, dry completely, and spray with a quality, fast dry, spray paint.

The installation of your ThruWall™ fan is not difficult, but the cutouts must be accurate.

In the carton you will find:

- (1) Telescoping metal sleeve with plastic grille attached.
- (1) Telescoping metal sleeve without grille attached.
- (1) Loose grille.
- (6) #6 Screws.
- (6) Wall Anchors.

Operation Instructions:

The ThruWall™ is equipped with a two speed motor. There is a three position switch on the output side of the fan. The switches: position (I) is low speed, center (O) off, and position (II) is high speed.

STEP BY STEP INSTALLATION INSTRUCTIONS

Step 1. Place the metal sleeve (without the grille attached) against the wall with the flanged edge facing you. Trace the pipe on the outside with a pencil to mark the cutout. (Refer to picture 1)

Step 2. Cut out the circular opening with a small drywall saw. Cut inside the pencil line. Take care not to damage the edge of the drywall since you will be installing drywall anchors close to the hole to mount the grille. (Refer to picture 2)

Step 3. Project the edge of the cutout onto the inside of the other wall board in three places, approximately 120° apart. Use a small square or a piece of cardboard that has an exact 90° angle to mark the cutout points on the inside of the other wall. The two circular openings must be accurately aligned. (Refer to picture 3)

Step 4. Use a small sharp pin or very small drill bit (1/32" or smaller) to punch or drill these three marks to the outside of the other wall. (Refer to picture 4)

Step 5. Place the other sleeve, with grille attached, against the outside of the wall and center its location using the three markers that you have made, then trace the outside of the sleeve with a pencil. Cut the circular opening with a small drywall saw. Cut inside the pencil line. Take care not to damage the edge of the drywall. You will be installing drywall anchors close to the hole to mount the grille. (Refer to picture 5)

Step 6. Insert the metal sleeve with grille into the cutout opening (fan output side) and snug the flange up against the wall material, making sure that power cord is hanging straight down.

Step 7. Insert the other metal sleeve into the cutout opening (fan suction side) and snug the flange up against the wall material.

Step 8. Position the unattached plastic grille over the metal sleeve that was just inserted so that the Suncourt logo is at the bottom and one of the mounting holes is in the top center. Mark the location of all 3 wall anchors. Make sure that the grille ribs are nicely square with the floor.


Step 9. Mark the position for the wall anchors on the grille.

Step 10. Remove metal sleeve with grille attached and drill the holes on both sides of the wall for the anchors with a sharp 3/16" drill bit. Install wall anchors and after re-inserting metal sleeve with grille attached, screw the grilles down snugly.

DO NOT OVERTIGHTEN. (Refer to picture 6)



Pic. 1




Pic. 2



Pic.3



Pic. 4



Pic. 5



Pic. 6

CLEANING AND MAINTENANCE

Before cleaning the TW108 ThruWall Fan™ unplug or switch power off at the appropriate breaker. Dust may be removed from the exterior surfaces using a soft cloth, the round brush attachment of your vacuum cleaner, or using a cloth that has been lightly moistened with water and a mild, non-abrasive detergent.