

METER SOFTENER

MODEL NO. 140-29-450-S-4M

CAPACITY:

MIN. 360,000 grs. @ 10 lbs./cu.ft.
 MAX. 450,000 grs. @ 15 lbs./cu.ft.

FLOW RATE:

NORMAL 75 gpm.
 PEAK 140 gpm.
 BACKWASH 25 gpm.

TANK SIZE: 30" x 72"

COMPOSITE

MEDIA:

RESIN 15 cu.ft.
 GRAVEL 350 lbs.

PIPE SIZE:

INLET 2"
 OUTLET 2"
 DRAIN 1"
 BRINE 1/2"
 METER 2"

NOTE:

ALL DASHED PIPE, VALVES,
 AND FITTINGS NOT PROVIDED
 BY US WATER SYSTEMS

BRINE TANK

TANK SIZE: 39" x 48"
 POLYETHYLENE

CAPACITY:

250 gals.
 2200 lbs./salt

BRINE VALVE: 454HF


BRINE WELL: 5"

SPACE REQUIRED (APPROX)
 73"L x 39"W x 88"H

PEAK FLOWS ARE NOT
 RECOMMENDED FOR EXTENDED
 PERIODS OF TIME.


WEIGHT (APPROX)

TOTAL SHIPPING 1,580 lbs.
 TOTAL OPERATING 4,200 lbs.



DO NOT SCALE DRAWING

THIS DRAWING IS ISSUED IN CONFIDENCE AND
 CANNOT BE REPRODUCED OR USED TO
 MANUFACTURE ANYTHING SHOWN OR REFERRED
 TO WITHOUT DIRECT WRITTEN PERMISSION FROM
 US WATER SYSTEMS

		US WATER SYSTEMS 1209 COUNTRY CLUB RD INDIANAPOLIS, IN 46234 1-800-608-8792
GENERAL ARRANGEMENT DWG. SOFTENER 450K SYSTEM 4- METER		
DRAWN BY: M. CURTIS DATE: CHECKED BY: PAGE 1 OF 1	DWG. NO. 140-29-450-S-4M	