



Yamaha G29 Seat Set Installation Guide

Tools Needed

- Clean Workspace
- Socket Wrench
- Safety Glasses
- Allen Wrench

Hardware Contents

- (4) 11/16" Spacers
- (4) Back Rest Washers
- (4) 2.5" Back Rest Bolts
- (8) Seat Hinge Washers

Missing hardware? Call 855-732-8669 - we'll send right away at no cost to you



Old Seat Removal

- Detach the back rest from the cart frame by removing the 4 bolts. These bolts can be discarded as they will be replaced with the provided screws from the hardware pack.
- Pull your seat cushion forward and lift away from the hinge receivers on the cart. Detach each hip restraint and seat hinge from the seat by removing each bolt. Set all components (bolts included) aside for installation with the new cushion.

NOTE: To ensure a clean seat installation, use soap and warm water to remove any dirt build up from your hip restraints before mounting to your new seat cushion

Seat Hinges

NOTE: The washers are used to stage each seat hinge so that the seat cushion folds down properly with a flush fit.

Center (2) washers above each bolt hole on left side for hinge installation. Place seat hinge on top of stacked washers and hand tighten with original hinge bolts. Ensure a parallel alignment with the seat board and complete mounting process using allen wrench. Repeat on right side.

Hip Restraints

Line up the short restraint (driver's side) with the hole pattern on the new seat board. Using original restraint bolts, hand tighten each bolt to ensure a proper alignment. Once all 4 bolts are in place, complete mounting process using socket wrench. Repeat step for long restraint (passenger's side).

Seat Cushion

After hinges and restraints are mounting to your seat cushion, you're ready to place on your golf cart. Line each hinge up with the receiver brackets on the cart and place into the slots. Gently lower the cushion so that the seat folds down.

Back Rest

Place washer on each back rest bolt prior to inserting into cart frame. Start with top left bolt hole, and place bolt into frame. Place spacer onto bolt before inserting into new back rest. Hand tighten. Repeat for bottom right bolt hole and again for top right and bottom left. Once all 4 bolts have been set, complete mounting process with socket wrench.

Golf Seat Cover Installation Guide

Step 6

Now your cover is ready for fastening around the rest of the cushion. Pull material tightly and begin on the bottom side of the cushion and place a staple every half inch or so. When you reach your corners, the vinyl may roll up with excess material. Pull the slack from the first roll and staple down. Repeat until the corners are smoothed out. Continue stapling down each side and corner of the cushion until you have reached the starting point.



Step 7

Check all sides to make sure that edge creases weren't created during stapling. If so, you can remove staples from the effected area and rework that material to smooth out. Replace any staples removed. Double check the upholstered side of the cushion to ensure you are wrinkle free.



Step 8

Once your cover has a smooth, tight fit around the cushion, you're ready to trim the excess material. Using your razor utility knife, carefully cut loose material above the staples around the inside of the seat. Once complete, you're ready to install your seat cushion to your cart.



Cover Install Complete

