



EN 1092-1-01 PN10

Tubo MM

DIN 2576 - PN10

Acero Inoxidable 1.4307 / A-304L

Acero Inoxidable 1.4404 / A-316L

Tipo A (cara plana)

DN	Tubo A	Brida				Tornillo			Peso kg/u.	
		B1	D	C1	K	Cant.	Rosca	L		
PN10 = PN16 = PN25 = PN40	15	18	18,5	95	14	65	4	M12	14	0,68
	20	23	23,5	105	16	75	4	M12	14	0,96
	25	28	28,5	115	16	85	4	M12	14	1,15
	32	38	38,5	140	(16) 18	100	4	M16	18	1,87
	40	43	43,5	150	(16) 18	110	4	M16	18	2,14
	50	53	53,5	165	(18) 20	125	4	M16	18	2,84
PN10 = PN16	65	73	73,7	185	(18) 20	145	(4) 8	M16	18	3,23
	80	84	84,7	200	20	160	8	M16	18	3,73
	100	104	104,8	220	(20) 22	180	8	M16	18	4,73
	125	129	130,0	250	22	210	8	M16	18	5,84
	150	154	156,0	285	(22) 24	240	8	M20	22	7,85
PN10	200	204	206,0	340	24	295	8	M20	22	10,26
	250	254	256,0	395	26	350	12	M20	22	13,57
	300	304	307,0	445	26	400	12	M20	22	15,70

(*) Medidas entre paréntesis según norma DIN2576 PN10