

## PIE DE MÁQUINA / MACHINE BASE / PIED MACHINE / MASCHINENFÜSSE

|  | REF / ART.NR       | DIMENSIONES / DIMENSIONS<br>ABMESSUNGEN |      |      |       | COMPRESION / COMPRESSION<br>DRUCKBELASTUNG |  |
|--|--------------------|---|------|------|-------|--|--|
|  |                    | ØA                                      | B    | D    | C     | CARGA / LOAD<br>CHARGE / LAST              | FLECHA / DEFLECTION<br>FLECHE / FEDERWEG |
|  |                    | mm.                                     |      |      |       | kg.  | mm.                                      |
| <b>S</b>   | <b>000</b>         | 40                                      | 23   | M-08 | 55    | 60   | 3,5±0,5                                  |
|  | <b>00</b>          | 60                                      | 28   | M-10 | 80    | 160  | 4,0±1,0                                  |
|  | <b>0</b>           | 70                                      | 32   | M-12 | 100   | 300  | 4,5±1,0                                  |
|  | <b>1</b>           | 85                                      | 30   | M-12 | 100   | 500  | 4,5±1,0                                  |
|  | <b>2</b>           | 100                                     | 40   | M-14 | 110   | 600  | 6,0±1,0                                  |
|  | <b>3</b>           | 120                                     | 50   | M-16 | 120   | 900  | 7,5±1,0                                  |
|  | <b>4</b>           | 140                                     | 50   | M-16 | 120   | 1.200                                      | 8,0±1,0                                  |
|  | <b>5</b>           | 160                                     | 60   | M-16 | 120   | 1.750                                      | 9,0±1,0                                  |
|  | <b>6</b>           | 180                                     | 70   | M-24 | 136   | 2.500                                      | 11,0±1,5                                 |
|  | <b>7</b>           | 205                                     | 75   | M-24 | 136   | 3.500                                      | 12,0±2,0                                 |
| <i>DUREZA / HARDNESS / DURETE / HÄRTE 60 SHÖRE</i> |                    |   |      |      |       |  |  |
| <b>S-B</b>   | <b>00-B</b>        | 60                                      | 18   | M-10 | 80    | 200  | 2,0±0,5                                  |
|  | <b>0-B</b>         | 70                                      | 20   | M-12 | 100   | 350  | 2,0±0,5                                  |
|  | <b>1-B</b>         | 85                                      | 25   | M-12 | 100   | 600  | 2,2±0,5                                  |
|  | <b>2-B</b>         | 100                                     | 20   | M-14 | 110   | 800  | 2,5±0,5                                  |
|  | <b>3-B</b>         | 120                                     | 25   | M-16 | 120   | 1.100                                      | 2,5±0,5                                  |
|  | <b>4-B</b>         | 140                                     | 33   | M-16 | 120   | 2.000                                      | 3,5±0,5                                  |
| <b>5-B</b>   | 160                | 31                                      | M-16 | 120  | 3.000 | 4,0±1,0                                    |  |
| <i>DUREZA / HARDNESS / DURETE / HÄRTE 75 SHÖRE</i> |                    |   |      |      |       |  |  |
| <b>AS</b>  | <b>AS4020-60SH</b> | 40                                      | 20   | M-08 | 40    | 90   | 4,0±0,5                                  |
|  | <b>AS5020-45SH</b> | 52                                      | 20   | M-10 | 70    | 180  | 4,0±1,0                                  |
|  | <b>AS6020-60SH</b> | 52                                      | 20   | M-10 | 70    | 275  | 4,0±1,0                                  |
|  | <b>AS6520-75SH</b> | 52                                      | 20   | M-12 | 90    | 750  | 4,0±1,0                                  |
|  | <b>AS7526-60SH</b> | 69                                      | 26   | M-12 | 80    | 330  | 5,0±1,0                                  |
|  | <b>AS8026-75SH</b> | 69                                      | 26   | M-12 | 80    | 550  | 5,0±1,0                                  |

