



# Diving Equipment Company of America

Remit to: PO Box 467, Santa Maria, CA. 93454 USA

2335 Meredith Lane, Santa Maria, California, 93455 USA

Ph: (805) 928-4500 Fax: (805) 928-4570 E-mail: Sales@decadiving.com

WebSite: <http://www.decadiving.com>

## DECA® Three Stage Filtration System (BT3-Assy.)

The BT 3-Assy. filtration system consists of three canister assemblies. Each canister is made of powder-coated die cast aluminum with 1" flow ports. The first and second stage canisters are fitted with auto drains and the third has a manual drain. The unit is plumbed with brass fittings, stainless steel hardware, and stainless steel gauges. The assembly is mounted inside a powder-coated aluminum frame. The unit is shipped ready to use with #10 JIC Male fittings on the inlet and outlet valves.



### Standard Features

- Two Inlets & Two Outlets (#10 JIC)
- 1/2" Brass Ball Valves
- Inlet/Outlet gauges 0-300 SS housing
- Brass Plumbing
- Stainless Steel Hardware
- L 30" x W 12" x H 16"
- Weight: 32 lbs.

### Element Specs

- Norgren 1<sup>st</sup> Stage: **F17-800-A1-DA** Filter Assy. w/ filter & auto drain
  - Filter replacement: **5311-01** 5 Micron (optional 40 Micron)
- Norgren 2<sup>nd</sup> Stage: **F46-800-AO-MA** Filter Assy. w/ filter & auto drain
  - Filter replacement: **5351-03** Oil Removal
- Norgren 3<sup>rd</sup> Stage: **F46-827-MA-MA** Filter Assy. w/ filter & manual drain
  - Filter replacement: **665-70** Charcoal, Water Vapor and Odor removal



(1<sup>st</sup> Stage Filter)



(2<sup>nd</sup> Stage Filter)



(3<sup>rd</sup> Stage Filter)

