

	Screen Size	65	55	49	43	32
	Panel Technology	IPS (PD)				
	Aspect Ratio	16 : 9				
	Native Resolution	1,920 x 1,080 (FHD)				
PANEL	Brightness	400cd/m ²	350cd/m ²			
	Contrast Ratio	1,300:1	1,100:1			
	Dynamic CR	500,000:1				
	Viewing Angle(H x V)	178 x 178				
	Surface Treatment	Hard coating (3H), Anti-glare treatment of the front polarizer (Haze 1 % (Typ.))				
	Battery life	18 Hours				
	Orientation	Portrait & Landscape				
	CONNECTIVITY	Input	HDMI, DVI-D, RGB, Stereo Mini Jack, USB (2)			
Output		Stereo Mini Jack, External Speaker Out				
External Control		RS232C (In/Out), RJ45, IR Receiver				
PHYSICAL SPECIFICATION	Bezel Color	Black				
	Bezel Width	11.9mm (T/R/L), 18mm (B)	11.9mm (T/R/L), 18mm (B)	11.9mm (T/R/L), 18mm (B)	11.9mm (T/R/L), 18mm (B)	13mm (T/R/L), 18mm (B)
	Monitor Dimensions (W x H x D)	1,456.9 x 838 x 41.1mm	1,238 x 714.9 x 38.6mm	1,102.2 x 638.5 x 38.6mm	969.6 x 563.9 x 38.6mm	729.4 x 428.9 x 55.5mm
	Weight (Head)	27.7kg	17.3kg	14.1kg	9.8kg	5.2kg
	Weight (Head + Stand)	32.9kg	20.6kg	17.4kg	12.3kg	6kg
	Monitor with Optional Stand & Speaker Dimensions (W x H x D)	1,456.9 x 898.1 x 293.7mm	1,238 x 773.4 x 219.6mm	1,102.2 x 696.8 x 219.6mm	969.6 x 622.2 x 193mm	729.4 x 481 x 154.2mm
	Weight (Head + Stand + Speaker)	33.4kg	21.1kg	17.9kg	12.8kg	6.5kg
	Carton Dimensions (W x H x D)	1,561 x 951 x 170mm	1,330 x 813 x 151mm	1,197 x 760 x 134mm	1,052 x 650 x 123mm	810 x 510 x 132mm
	Packed Weight	33.6kg	21.5kg	17.1kg	12.4kg	6.5kg
	VESA™ Standard Mount Interface	300 x 300			200 x 200	
SPECIAL FEATURES	USB Content Scheduling, Conformal Coating, SNMP Support, Wi-Fi Ready (Dongle), Power Management modes (Sustain Aspect Ratio/Stand-by Screen, etc.), No Signal Image setting, Enhanced ISM (Image Sticking Minimization) Mode, Holiday Schedule/Local Time Auto Setting, Fail-over (USB, RGB, DVI, HDMI), Wake on LAN					
ENVIRONMENTAL CONDITIONS	Operating Temperature range	0 °C to 40 °C	0 °C to 40 °C	0 °C to 40 °C	0 °C to 40 °C	0 °C to 40 °C
	Operating Humidity range	10 % to 80 %	10 % to 80 %	10 % to 80 %	10 % to 80 %	10 % to 80 %
POWER	Power Supply	100-240V-, 50/60Hz				
	Power Type	Built-In Power				
POWER CONSUMPTION	Typ.	95W	70W	65W	60W	50W
	Smart Energy Saving	70W	55W	50W	45W	35W
STANDARD (CERTIFICATION)	Safety	UL / cUL / CB / TUV / KC				
	EMC	FCC Class "A" / CE / KCC				
	ErP / Energy Star	Yes / Yes (Energy Star 6.0)				
MEDIA PLAYER COMPATIBILITY	External Media player Attachable	Yes (MP500/MP700)	Yes (MP500/MP700)	Yes (MP500/MP700)	Yes (MP500/MP700)	No
SOFTWARE COMPATIBILITY	SuperSign-w lite	Yes				
	SuperSign-c	Yes				
	Basic	Remote Controller (2 batteries included), Power Cord, QSG, RGB Cable, Regulation Book, Phone to RS232C Gender				
		Speaker (SP-5000),	Speaker (SP-5000),	Speaker (SP-5000),	Speaker (SP-5000),	Speaker (SP-5000)