



**Dongguan Hinen New Energy Technology Co., Ltd**

Add: No.24 Dongkang Road, Dalingshan Town,  
Dongguan City, Guangdong Province, China  
Tel: +86 (769) 8992 0666  
Email: market@hinen.com  
Website: <https://www.hinen.com>

**Australian Authorized Importer:**

Company name: HINEN AUSTRALIA PTY LTD  
Contact Person: Steve  
Address: Level 5, Tenancy 3, 107 Mount Street, North Sydney.  
Phone: +61 478175078  
Email: service@hinen.com.au  
Website: <https://www.hinen.com>



# 5000Wh BATTERY SYSTEM(AU) Datasheet



DC/AC ratio up to 190%



Max. MPPT current reaching 16A for a single PV string



The shell adopts integrated die-casting



Ultra-quiet  $\leq 25$ dB



EPS, Max. Back-up switch time  $\leq 20$ ms



Charge up to 120A(continuous) / discharge up to 120A(continuous)

## Technical parameters

Model	B5000 x1	B5000 x2	B5000 x3	B5000 x4
Product name	Rechargeable Li-ion Battery Pack (5.12kWh)	Rechargeable Li-ion Battery Pack (10.24kWh)	Rechargeable Li-ion Battery Pack (15.36kWh)	Rechargeable Li-ion Battery Pack (20.48kWh)
Rated Energy <sup>1</sup>	5.12kWh	10.24kWh	15.36kWh	20.48kWh
Usable capacity	4.6kWh	9.21kWh	13.82kWh	18.43kWh
Battery type	LFP(LiFePO <sub>4</sub> )			
Battery configuration	16S1P	16S2P	16S3P	16S4P
Maximum modules in parallel	4			
Cycle life <sup>2</sup>	8000 cycles			
Rated voltage	51.2 V			
Operating voltage range	40~57.6 V			
Peak current	120A 60S			
Depth of Discharge (DOD)	90%	90%	90%	90%
Max. continuous charge / discharge current	100A	120A	120A	120A
Rated power	5.12KW	6.14KW	6.14KW	6.14KW
Short-Circuit Current	800A@0.1mS			
Run Log Recording	32M-byte			
Communication	CAN			
Weight	51.8KG	103.6KG	155.4KG	207KG
Dimensions (W*H*D)	579*500*175mm	579*1000*175mm	579*1500*175mm	(579*1000*175mm) x2
Operating temperature	Charge: 0°C < T < 55°C / Discharge: -20°C < T < 55°C			
Storage temperature	-20~40°C (≤ One month) / 0~35°C (≤ One year)			
Humidity	≤ 10~85%			
Altitude	≤ 2000m			
Ingress protection rating	IP65			
Installation type	Wall-mounted/ Floor stand			
Warranty <sup>3</sup>	10 Years Warranty, 10 Years Performance Life			
Country of manufacture	Made in China			

Rated Energy<sup>1</sup>: Test conditions: Fresh battery 0.33C charge & discharge at +25±3°C.

Cycle life<sup>2</sup>: Test conditions, 90%DOD, 0.2C charge & discharge at +25±3°C.

Warranty<sup>3</sup>: Refer to battery warranty letter for conditional application.

# hinen

Text and images correspond to the current state of technology at the time of printing. hinen reserves the right of final interpretation of this document and all documents related to this product, which may be updated, revised or terminated without notice.