



AF2908612102

7FRO2912

Industrial-Maid
351 S. 12th Rd.
Cortland, Nebraska 68331

TF: 1-877-624-3247
Fax: 402-798-7117
www.industrial-maid.com

FR Cell/Poly Blend Cartridge

All filters are made from a premium blend of flame retardant cellulose and polyester. This material is especially designed for back pulse operations, and offers enhanced stability and structural integrity. All cellulose blend filters are dimpled pleated. This pleat lock helps maintain pleat spacing during operation.



Height:	11.5"
Outside Diameter:	12"
Inside Diameter:	6"
Style:	Open/Closed
Gasket:	.5" x .5" Natural Rubber
Pleat Count:	225
Pleat Depth:	3"
Pleat Spacing:	Pleat lock
Filtration Area:	107 Sq.ft.
Filter Media:	FR Cell/Poly Blend
Inner Cage:	Galv. Expanded Metal 72% Open
Outer Cage:	Galv. Expanded Metal 72% Open
End Caps:	Galvanized Metal
Pleat/End Cap Bonding:	Urethane
Nominal Air Flow:	225 cfm
Nominal Resistance:	1.0" wg
Efficiency:	99 @ .5 micron
Max. Operating Temp:	180°F
Shipping Weight	11 lbs



2908612102

