



SHEET TITLE : 3000i
 DRWG. NO.: 30I-0820 DRAWN BY: TAA
 DATE: 08/20/20 SCALE: NTS

SPECIFICATIONS:

- DIMENSIONS:** 25" H X 72" W X 25" D
- MOTOR:** 3/4 HP, 115/1/60 2 speed, 9.1 FLA
 3/4 HP, 208-230/1/60 2 speed, 4.0 FLA
- CFM:** HIGH - 3000 CFM @ .6 W.G.
 LOW - 2600 CFM @ 0.4" W.G.
- ELECTRICAL:** 115V - SWITCH & 15' CORD
 230V - WIRED TO JCT. BOX
- BLOWER:** DIRECT DRIVE FORWARD CURVE
- CONSTRUCTION:** 12 & 14 GA POWDER COATED STEEL
 16 GA. BRONZE HAMMERTONE
 POWDER COATED STEEL PANELS
 4-WAY ALUMINUM EXHAUST GRILLE
 NEEDLEPOINT BIPOLAR IONIZATION
 MODULE, 10 WATTS
 AUTO CLEANING IONIZER
- STD. FILTERS:** (2) 4" MERV 10 PLEATED PREFILTER
 (2) MERV 15 MAIN FILTER
 (2) 2" CARBON
 (1) NPBI IONIZER MODULE
- OPTIONS:** EYEBOLTS (INSTALLED)
 SILENCER
 MANOMETER PRESSURE GAUGE
 2" POLY PAD - FILTER SAVERS
 HEPA FILTER - 99.97% @ .3 MICRON
- WEIGHT:** 170 LBS.
- NOISE:** HIGH - 63.4 dBA
 LOW - 59 dBA

DISTRIBUTED BY:

COPYRIGHT: This document and the information contained may not be reproduced or distributed without express written consent of INDUSTRIAL MAID. Unauthorized reproduction, disclosure, or manufacturing use are prohibited by copyright law.

INDUSTRIAL MAID
 INDUSTRIAL MAID LLC
 351 S. 12TH RD.
 CORTLAND, NE 68331
 Ph. (402) 798-7116
 Fax (402) 798-7117
 www.industrial-maid.com