

mation contained may not be reproduced or distributed without express written consent of INDUSTRIAL MAID. Unauthorized reproduction, disclosure, or manufacturing use are prohibited by copyright law.

SHEET TITLE: AZTech RH35-2

DRWG. NO.:RH32-0518

DRAWN BY:TAA

DATE: 05/08/18

SCALE: NTS

SPECIFICATIONS:

DIMENSIONS: RH35-2 36.5"H X 134" W X 63" D

MOTOR: 3/4 HP 115/1/60, 10.2 FLA 2 HP 208-230/460/3/60 TEFC

> 6.0-5.8/2.9 FLA 3 HP 230/460/3/60 TEFC

8.6/4.3 FLA

CFM: 3/4 HP - 3000 CFM @ .5" W.G. 2 HP - 3500 CFM @ 1.0" W.G.

3 HP - 4450 CFM @ 1.0" W.G. CONSTRUCTION 11,14, & 16 GA POWDER COATED ST.

FRAME.

16 GA STEEL PANELS DUST PROOF LED LIGHT KIT

4-WAY ALUMINUM EXHAUST GRILLE

ELECTRICAL WIRED TO JCT. BOX

OPT. MOTOR STARTER AVAILABLE

10 X 10 FORWARD CURVED BLOWER 3/4 HP - DIRECT DRIVE BLOWER:

2 & 3 HP - BELT DRIVE

2" GALV. BAFFLE PREFILTER OPT. 2" ALUMINUM MESH FILTERS:

4" PLEATED PREFILTER

95% FIBERGLASS BAG FILTER

HEPA AFTER FILTER SILENCER OPTIONS:

MAGNAHELIC PRESSURE GAUGE MACHINE LIFT EYES

CURTAIN ENCLOSURE

THERMAL SENSOR/ POWER CUT OFF

WEIGHT: DIRECT DRIVE 1115 LBS.

BELT DRIVE - 1139 LBS.

NOISE: 3/4 HP - 63.4 dBA

2 HP - 71.5 dBA 3 HP - 72.0 dBA



INDUSTRIAL MAID LLC 351 S. 12TH RD. CORTLAND, NE 68331 Ph. (402) 798-7116 Fax (402) 798-7117 www.indústrial-maid.com