



**INDUSTRIAL MAID**

# CARTRIDGE DATA SHEET

**CAC2921530101**

**Filter 1 #FLCA30CCLF2F**

**FR Cell/Poly Blend Cartridge**

Complete Filtration's filters are made from a premium blend of flame retardant cellulose and polyester media . This material is especially designed for back pulse operations, and offers enhanced stability and structural integrity. All cellulose blend filters are dimpled pleated. This pleat lock helps maintain pleat spacing during operation.



Height:	30"
Outside Diameter:	12.75"
Inside Diameter:	8.3"
Style:	Open/Closed
Top Gasket:	10.64 ½ x ½ Gasket
Bottom Gasket:	
Pleat Count:	314
Pleat Depth:	2"
Pleat Spacing:	Pleat lock
Filtration Area:	260 Sqft
Filter Media:	FR Cellulose Poly Blend
Inner Cage:	Galv. Expanded Metal 72% Open
Outer Cage:	Galv. Expanded Metal 72% Open
End Caps:	Galvanized Metal
Pleat/End Cap Bonding:	Urethane
Nominal Air Flow:	550 cfm
Nominal Resistance:	1.0" wg
Efficiency:	99% @ .5 micron
Max. Operating Temp:	180°F

2921530101

