

Industrial-Maid
 351 S. 12th Rd.
 Cortland, Nebraska 68331

TF: 1-877-624-3247
 Fax: 402-798-7117
 www.industrial-maid.com

TD1226926101-151244 /P151244-461-436

FR Cellulose-Polyester Blend Cartridge

Industrial Maid’s filters are made from a premium blend of flame retardant cellulose and polyester. This material is especially designed for back pulse operations, and offers enhanced stability and structural integrity. All cellulose blend filters are dimpled pleated. This pleat lock helps maintain pleat spacing during operation.



| | |
|------------------------|--------------------------------|
| Dimensions: | 12.74" x 8.38" x 26" |
| Style: | Open/Open |
| Gasket | .5"x .5" Molded Natural Rubber |
| Pleat Count: | 314 |
| Pleat Depth: | 2" |
| Pleat Spacing: | Pleat lock |
| Filtration Area: | 226 Sqft |
| Filter Media: | FR Cell/Poly Blend |
| Inner Cage: | Galv. Expanded Metal 72% Open |
| Outer Cage: | Galv. Expanded Metal 72% Open |
| End Caps: | Galvanized Metal |
| Pleat/End Cap Bonding: | Polyurethane |
| Nominal Air Flow: | 500 cfm |
| Nominal Resistance: | 1.0" wg |
| Efficiency: | 99.5% @ .5 Micron |
| Max. Operating Temp: | 180°F |
| | |
| | |



1226926101

