



TD3074716101-21586

Industrial-Maid  
351 S. 12th Rd.

TF: 1-877-624-3247  
Fax: 402-798-7117

**8PP-21586-00**

Cortland, Nebraska 68331 [www.industrial-maid.com](http://www.industrial-maid.com)

## FR Cellulose-Polyester Blend Cartridge

Industrial Maid’s filters are made from a premium blend of flame retardant cellulose and polyester. This material is especially designed for back pulse operations, and offers enhanced stability and structural integrity. All cellulose blend filters are dimpled pleated. This pleat lock helps maintain pleat spacing during operation.



|                        |                                |
|------------------------|--------------------------------|
| Dimensions:            | 7.93 OD X 3.64 ID X 16         |
| Style:                 | Open/Closed W/Bolt Hole        |
| Gasket                 | .5"x .5" Molded Natural Rubber |
| Pleat Count:           | 171                            |
| Pleat Depth:           | 2"                             |
| Pleat Spacing:         | Pleat lock                     |
| Filtration Area:       | 75 Sqft                        |
| Filter Media:          | FR Cell/Poly Blend             |
| Inner Cage:            | Galv. Expanded Metal 72% Open  |
| Outer Cage:            | Galv. Expanded Metal 72% Open  |
| End Caps:              | Galvanized Metal               |
| Pleat/End Cap Bonding: | Polyurethane                   |
| Nominal Air Flow:      | 300 cfm                        |
| Nominal Resistance:    | 1.0" wg                        |
| Efficiency:            | 99% @ .5 Micron                |
| Max. Operating Temp:   | 180°F                          |
|                        |                                |
|                        |                                |



3074716101

